

7851A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable



For more Information
please call

1-800-Belden1



Description:

23 AWG Bonded-Pairs, Solid Bare Copper Conductors, Non-Plenum, Polyolefin Insulation, Patented e-Spline Center Member, Rip Cord, PVC Jacket

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors: 8

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
5.766
8.001

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Separator Material: Patented E-Spline Center Member

Overall Nominal Diameter: 5.766 x 8.001 mm

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)

7851A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

Storage Temperature Range:	-20°C To +75°C
Installation Temperature Range:	-20°C To +75°C
Operating Temperature Range:	0°C To +75°C
Bulk Cable Weight:	52.087 Kg/Km
Max. Recommended Pulling Tension:	200.169 N
Min. Bend Radius/Minor Axis:	50.800 mm
Min. Bend/Installation:	58.420 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
NEC Articles:	800
CEC/C(UL) Specification:	CMR
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class E
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2
Other Specification:	UL Verified to Category 6

Applicable Patents:

Country	Patent
US	5606151
US	5734126
US	6074503
US	6855889
US	7663061
US	7838773
US	7977575

Flame Test

UL Flame Test:	UL1666 Vertical Riser
C(UL) Flame Test:	FT4
CSA Flame Test:	FT4
IEEE Flame Test:	1202

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Burial:	No
Sunlight Resistance:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	7852A

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/m)
50.8555

Maximum Capacitance Unbalance (pF/100 m): 90

Nominal Velocity of Propagation:

VP (%)
67

Maximum Delay:

Delay (ns/100 m)
538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
38

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
8.2

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
1	1.9	82.3	80.3	80.5	78.5	20.0	27.0
4	3.6	73.3	71.3	69.7	67.7	23.0	27.0
8	5.1	68.8	66.8	63.7	61.7	24.5	27.0
10	5.7	67.3	65.3	61.6	59.6	25.0	27.0
16	7.2	64.3	62.3	57.0	55.0	25.0	27.0
20	8.1	62.8	60.8	54.7	52.7	25.0	27.0
25	9.1	61.3	59.3	52.3	50.3	25.0	27.0
31.25	10.2	59.9	57.9	49.7	47.7	25.0	27.0
62.5	14.7	55.4	53.4	40.7	38.7	25.0	27.0
100	18.9	52.3	50.3	33.4	31.4	25.0	27.0
155	23.9	49.5	47.5	25.5	23.5	22.8	24.7
200	27.5	47.8	45.8	20.3	18.3	21.7	23.4
250	31.2	46.3	44.3	15.2	13.2	20.5	22.2
300	34.5	43.2	41.2	10.6	8.6	20.2	21.2
310	35.2	42.9	40.9	9.8	7.8	20.1	21.1
350	37.7	42.2	40.2	6.5	4.5	19.8	20.4
400	40.6	41.3	39.3	2.6	0.6	19.5	19.7
450	43.5	40.5	38.5	2.1	0.10	18.9	19.1
460	44.0	40.4	38.4	0	0	18.8	19.0
500	46.2	39.8	37.8			18.4	18.5
550	48.8	39.2	37.2			18.0	18.0
600	51.4	38.6	36.6			17.6	17.6

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	100 ± 15	73.8	70.8
4	100 ± 12	100 ± 10.4	61.8	58.8
8	100 ± 12	100 ± 8	55.7	52.7
10	100 ± 12	100 ± 7.3	53.8	50.8

7851A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

16	100 ± 12	100 ± 5.7	49.7	46.7
20	100 ± 12	100 ± 5	47.8	44.8
25	100 ± 15	100 ± 5	45.8	42.8
31.25	100 ± 15	100 ± 5	43.9	40.9
62.5	100 ± 15	100 ± 5	37.9	34.9
100	100 ± 15	100 ± 5	33.8	30.8
155	100 ± 15	100 ± 5	30.0	27.0
200	100 ± 15	100 ± 5	27.8	24.8
250	100 ± 20	100 ± 5	25.8	22.8
300	100 ± 20	100 ± 5	24.3	21.3
310	100 ± 20	100 ± 5	24.0	21.0
350	100 ± 22	100 ± 5	22.9	19.9
400	100 ± 22	100 ± 5	21.8	18.8
450	100 ± 22	100 ± 5	20.7	17.7
460	100 ± 22	100 ± 5	20.5	17.5
500	100 ± 22	100 ± 5	19.8	16.8
550	100 ± 22	100 ± 5	19.0	16.0
600	100 ± 22	100 ± 5	18.2	15.2

Notes (Overall)

Notes: Belden IBDN. Jacket sequentially marked at 2 ft/1m intervals. Third party verified to ANSI/TIA-568-C.2, Category 6.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7851A F6HA1000	305 MT	17.690 KG	GRAY, DARK PEARL		CAT6E+ 4PRB U/UTP CMR RIB
7851A F6H1000	305 MT	16.329 KG	GRAY, DARK PEARL	C	CAT6E+ 4PRB U/UTP CMR REEL
7851A 002A1000	305 MT	17.690 KG	RED		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0021000	305 MT	16.329 KG	RED		CAT6E+ 4PRB U/UTP CMR REEL
7851A 003A1000	305 MT	17.690 KG	ORANGE		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0031000	305 MT	16.329 KG	ORANGE	C	CAT6E+ 4PRB U/UTP CMR REEL
7851A 004A1000	305 MT	17.690 KG	YELLOW		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0041000	305 MT	16.329 KG	YELLOW	C	CAT6E+ 4PRB U/UTP CMR REEL
7851A 005A1000	305 MT	17.690 KG	GREEN, DARK		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0051000	305 MT	16.329 KG	GREEN, DARK	C	CAT6E+ 4PRB U/UTP CMR REEL
7851A 006A1000	305 MT	17.690 KG	BLUE, LIGHT		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0061000	305 MT	16.329 KG	BLUE, LIGHT	C	CAT6E+ 4PRB U/UTP CMR REEL
7851A 009A1000	305 MT	17.690 KG	WHITE		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0091000	305 MT	16.329 KG	WHITE	C	CAT6E+ 4PRB U/UTP CMR REEL
7851A 010A1000	305 MT	17.690 KG	BLACK		CAT6E+ 4PRB U/UTP CMR RIB
7851A 0101000	305 MT	16.329 KG	BLACK		CAT6E+ 4PRB U/UTP CMR REEL

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 6 Revision Date: 07-10-2012

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

METRIC MEASUREMENT VERSION

7851A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А