

ADD-A-PAK Generation VII Power Modules Standard Diodes, 100 A



ADD-A-PAK


RoHS
COMPLIANT

FEATURES

- High voltage
- Industrial standard package
- UL approved file E78996 
- Low thermal resistance
- Designed and qualified for industrial level
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912

BENEFITS

- Excellent thermal performances obtained by the usage of exposed direct bonded copper substrate
- Up to 1600 V
- High surge capability
- Easy mounting on heatsink

ELECTRICAL DESCRIPTION

These modules are intended for general purpose high voltage applications such as high voltage regulated power supplies, lighting circuits, temperature and motor speed control circuits, UPS and battery charger.

| PRODUCT SUMMARY | |
|-----------------|-------------------------------|
| $I_{F(AV)}$ | 100 A |
| Type | Modules - Diode, High Voltage |

MECHANICAL DESCRIPTION

The ADD-A-PAK generation VII, new generation of ADD-A-PAK module, combines the excellent thermal performances obtained by the usage of exposed direct bonded copper substrate, with advanced compact simple package solution and simplified internal structure with minimized number of interfaces.

| MAJOR RATINGS AND CHARACTERISTICS | | | |
|-----------------------------------|-----------------|-------------|--------------------|
| SYMBOL | CHARACTERISTICS | VALUES | UNITS |
| $I_{F(AV)}$ | 112 °C | 100 | A |
| $I_{F(RMS)}$ | | 157 | |
| I_{FSM} | 50 Hz | 2020 | |
| | 60 Hz | 2115 | |
| I^2t | 50 Hz | 20.41 | kA ² s |
| | 60 Hz | 18.63 | |
| $I^2\sqrt{t}$ | | 204.1 | kA ² √s |
| V_{RRM} | Range | 400 to 1600 | V |
| T_J | | - 40 to 150 | °C |
| T_{Stg} | | | |



ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS | | | | |
|------------------------|--------------|---|---|---|
| TYPE NUMBER | VOLTAGE CODE | V _{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V | V _{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V | I _{RRM} MAXIMUM AT T _J = 150 °C mA |
| VS-VSK.91 | 04 | 400 | 500 | 10 |
| | 06 | 600 | 700 | |
| | 08 | 800 | 900 | |
| | 10 | 1000 | 1100 | |
| | 12 | 1200 | 1300 | |
| | 14 | 1400 | 1500 | |
| | 16 | 1600 | 1700 | |

| FORWARD CONDUCTION | | | | | |
|---|---------------------|--|----------------------------------|--------|--------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum average forward current at case temperature | I _{F(AV)} | 180° conduction, half sine wave | | 100 | A |
| | | | | 112 | °C |
| Maximum RMS forward current | I _{F(RMS)} | DC at 90 °C case temperature | | 157 | |
| Maximum peak, one-cycle forward, non-repetitive surge current | I _{FSM} | t = 10 ms | No voltage reapplied | 2020 | A |
| | | t = 8.3 ms | | 2115 | |
| | | t = 10 ms | 100 % V _{RRM} reapplied | 1700 | |
| | | t = 8.3 ms | | 1780 | |
| Maximum I ² t for fusing | I ² t | t = 10 ms | No voltage reapplied | 20.41 | kA ² s |
| | | t = 8.3 ms | | 18.63 | |
| | | t = 10 ms | 100 % V _{RRM} reapplied | 14.44 | |
| | | t = 8.3 ms | | 13.18 | |
| Maximum I ² √t for fusing | I ² √t | t = 0.1 ms to 10 ms, no voltage reapplied | | 204.1 | kA ² √s |
| Low level value of threshold voltage | V _{F(TO)1} | (16.7 % × π × I _{F(AV)} < I < π × I _{F(AV)}), T _J = T _J maximum | | 0.76 | V |
| High level value of threshold voltage | V _{F(TO)2} | (I > π × I _{F(AV)}), T _J = T _J maximum | | 0.89 | |
| Low level value of forward slope resistance | r _{f1} | (16.7 % × π × I _{F(AV)} < I < π × I _{F(AV)}), T _J = T _J maximum | | 2.4 | mΩ |
| High level value of forward slope resistance | r _{f2} | (I > π × I _{F(AV)}), T _J = T _J maximum | | 2.05 | |
| Maximum forward voltage drop | V _{FM} | I _{FM} = π × I _{F(AV)} , T _J = 25 °C, t _p = 400 μs square wave | | 1.55 | V |

| BLOCKING | | | | | |
|--------------------------------------|------------------|-------------------------|--|--------------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum peak reverse leakage current | I _{RRM} | T _J = 150 °C | | 10 | mA |
| Maximum RMS insulation voltage | V _{INS} | 50 Hz | | 3000 (1 min) | V |
| | | | | 3600 (1 s) | |



| THERMAL AND MECHANICAL SPECIFICATIONS | | | | |
|---|----------------|--|-------------------------------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Junction and storage temperature range | T_J, T_{Stg} | | - 40 to 150 | °C |
| Maximum internal thermal resistance, junction to case per leg | R_{thJC} | DC operation | 0.22 | °C/W |
| Typical thermal resistance, case to heatsink per module | R_{thCS} | Mounting surface flat, smooth and greased | 0.1 | |
| Mounting torque $\pm 10\%$ to heatsink busbar | | A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. | 4 | Nm |
| | | | 3 | |
| Approximate weight | | | 75 | g |
| | | | 2.7 | oz. |
| Case style | | JEDEC® | ADD-A-PAK Gen. VII (TO-240AA) | |

| ΔR CONDUCTION PER JUNCTION | | | | | | | | | | | |
|------------------------------------|---------------------------|-------|-------|------|-------|-----------------------------|-------|-------|-------|-------|-------|
| DEVICES | SINE HALF WAVE CONDUCTION | | | | | RECTANGULAR WAVE CONDUCTION | | | | | UNITS |
| | 180° | 120° | 90° | 60° | 30° | 180° | 120° | 90° | 60° | 30° | |
| VSK.91 | 0.057 | 0.068 | 0.087 | 0.12 | 0.177 | 0.045 | 0.073 | 0.093 | 0.123 | 0.178 | °C/W |

Note

- Table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC



Fig. 1 - Current Ratings Characteristics



Fig. 4 - On-State Power Loss Characteristics



Fig. 2 - Current Ratings Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current



Fig. 3 - Forward Power Loss Characteristics



Fig. 6 - Maximum Non-Repetitive Surge Current



Fig. 7 - Forward Power Loss Characteristics



Fig. 8 - Forward Power Loss Characteristics



Fig. 9 - Forward Power Loss Characteristics



Fig. 10 - Forward Voltage Characteristics




Fig. 11 - Thermal Impedance Z_{thJC} Characteristics

ORDERING INFORMATION TABLE

| | | | | | | |
|-------------|--------------|----------|---|-----------|----------|-----------|
| Device code | VS-VS | K | D | 91 | / | 16 |
| | ① | ② | ③ | ④ | | ⑤ |
| | 1 | - | Vishay Semiconductors product | | | |
| | 2 | - | Module type | | | |
| | 3 | - | Circuit configuration (see Circuit Configuration table) | | | |
| | 4 | - | Current code (100 A) | | | |
| | 5 | - | Voltage code (see Voltage Ratings table) | | | |

Note

- To order the optional hardware go to www.vishay.com/doc?95172



| CIRCUIT CONFIGURATION | | |
|----------------------------|----------------------------|-----------------------|
| CIRCUIT DESCRIPTION | CIRCUIT CONFIGURATION CODE | CIRCUIT DRAWING |
| Two diodes doubler circuit | D | <p>VSKD...</p> |
| Two diodes common cathodes | C | <p>VSKC...</p> |
| Two diodes common anodes | J | <p>VSKJ...</p> |
| Single diode | E | <p>VSKE...</p> |

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|--|
| Dimensions | www.vishay.com/doc?95369 |

ADD-A-PAK Generation VII - Diode

DIMENSIONS in millimeters (inches)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А