


Programmable High Frequency Crystal Oscillator with Spread Spectrum (SSXO) and No Spread Spectrum (XO) Option

Features

- Crystal Oscillator with Spread Spectrum Clock (SSXO)
- No Spread Spectrum (XO) Option
- Wide operating output clock frequency range of 10 –166 MHz
- Programmable spread spectrum with nominal 31.5 kHz modulation frequency
- Center spread: $\pm 0.25\%$ to $\pm 2.0\%$
- Down spread: -0.5% to -4.0%
- No spread: $\pm 0.0\%$
- Integrated phase-locked loop (PLL)
- 85 ps typical cycle-to-cycle jitter with SSCLK = 133 MHz
- 3.3V operation
- Output enable function
- Package available in 4-Pin ceramic LCC SMD
- Pb-free package
- Industrial temperature from -40°C to 85°C

Benefits

- Provides a wide range of spread percentages for maximum electromagnetic interference (EMI) reduction to meet regulatory agency electromagnetic compliance (EMC) requirements. Reduces development and manufacturing costs and time-to-market.
- This versatile programming feature enables the user to switch between SSXO (with Spread) and XO (without Spread) functions with ease.
- Internal PLL to generate up to 166 MHz output.
- Suitable for most PC, consumer, and networking applications
- Application compatibility in standard and low-power systems
- In house programming of samples and prototype quantities is available using CY3672 programming kit and CY3724 socket adapters. Production quantities are available through Cypress' value added distribution partners or by using third party programmers from BP Microsystems, and HiLo Systems, and others.



Pin Definition

| Pin | Name | Description |
|-----|-------|---|
| 1 | OE | Output Enable pin: Active HIGH. If OE = 1, SSCLK is enabled |
| 2 | VSS | Power supply ground |
| 3 | SSCLK | Spread spectrum clock output (with or without spread) |
| 4 | VDD | 3.3V power supply |

Functional Description

The CY25701 is a Spread Spectrum Crystal Oscillator (SSXO) IC used to reduce the EMI found in today's high speed digital electronic systems.

The device uses a Cypress proprietary PLL and Spread Spectrum Clock (SSC) technology to synthesize and modulate the frequency of the embedded input crystal. By frequency modulating the clock, the measured EMI at the fundamental and harmonic frequencies are greatly reduced. This reduction in radiated energy can significantly reduce the cost of complying with regulatory agency (EMC) requirements and improve time-to-market without degrading system performance.

The CY25701 uses a programmable configuration memory array to synthesize output frequency and spread%.

The spread percentage is programmed to either center spread or down spread with various spread percentages. The range for center spread is from $\pm 0.25\%$ to $\pm 2.00\%$. The range for down spread is from -0.5% to -4.0% . Contact the factory for smaller or larger spread percentage amounts if required. Refer to [Table 2](#) for spread selection and no spread values.

The frequency modulated SSCLK output is programmable from 10 to 166 MHz.

The CY25701 is available in a 4-pin ceramic SMD package with an operating temperature range of -40 to 85°C .

Programming Description

Factory and Field Programmable CY25701

Factory and field programming is available for samples and manufacturing by Cypress and its distributors. Submit your request to the local Cypress Field Application Engineer (FAE) or sales representative. Once the request is processed, you will receive a new part number, samples, and data sheet with the programmed values. This part number is used for additional sample request and the production orders. Contact your local Cypress FAE or sales representative for details.

Additional information on the CY25701 is available at the Cypress web site www.cypress.com.

Output Frequency, SSCLK Output (SSCLK, pin 3)

The modulated frequency at the SSCLK output is produced by synthesizing from the embedded crystal oscillator frequency input. The range of synthesized clock is from 10 to 166 MHz.

Spread Percentage (SSCLK, pin 3)

The SSCLK spread is programmable to various spread percentage values from $\pm 0.25\%$ to $\pm 2.0\%$ for center spread and from -0.5% to -4.0% for down spread. Refer to [Table 2](#) for available spread options. Enter $\pm 0.0\%$ (No spread) for XO (crystal oscillator) without spread option.

Frequency Modulation (SSCLK, pin 3)

The default frequency modulation is programmed at 31.5 kHz for all SSCLK frequencies from 10 to 166 MHz. Alternate frequency modulations at 30.1 kHz or 32.9 kHz are selectable using CyberClocksOnline™ software. Contact the factory for other alternate modulation frequencies if required.

Table 1. Programming Data Requirement

| Pin Function | Output Frequency | Spread Percent Code ^[1] | Frequency Modulation |
|----------------------|-------------------|------------------------------------|------------------------|
| Pin Name | SSCLK | SSCLK | SSCLK |
| Pin# | 3 | 3 | 3 |
| Units | MHz | % | kHz |
| Program Value | ENTER DATA | ENTER DATA | ENTER DATA 31.5 |

Note

- $\pm 0.0\%$ or Code "Z" for XO (No-Spread) option.

Table 2. Spread Percent Selection

| | | | | | | | | |
|---------------|------------|--------|-------|--------|-------|-------|-------|-------|
| Center Spread | Code | A | B | C | D | E | F | Z |
| | Percentage | ±0.25% | ±0.5% | ±0.75% | ±1.0% | ±1.5% | ±2.0% | ±0.0% |
| Down Spread | Code | G | H | J | K | L | M | Z |
| | Percentage | -0.5% | -1.0% | -1.5% | -2.0% | -3.0% | -4.0% | ±0.0% |

Absolute Maximum Ratings

Supply Voltage (VDD).....-0.5V to +7.0V
 DC Input Voltage -0.5V to V_{DD} + 0.5V

Storage Temperature (Non-condensing) -55°C to +100°C
 Junction Temperature -40°C to +125°C
 Data Retention @ T_j = 125°C.....>10 years
 Package Power Dissipation..... 350 mW

Operating Conditions

| Parameter | Description | Min | Typ | Max | Unit |
|--------------------|---|------|------|------|------|
| V _{DD} | Supply voltage | 3.00 | 3.30 | 3.60 | V |
| T _A | Ambient temperature (commercial) | -20 | - | 70 | °C |
| T _A | Ambient temperature (industrial) | -40 | - | 85 | °C |
| C _{LOAD} | Max. load capacitance @ pin 3 | - | - | 15 | pF |
| F _{SSCLK} | SSCLK output frequency, C _{LOAD} = 15 pF | 10 | - | 166 | MHz |
| F _{MOD} | Spread Spectrum Modulation Frequency | 30.0 | 31.5 | 33.0 | kHz |
| T _{PU} | Power up time for VDD to reach minimum specified voltage (power ramp must be monotonic) | 0.05 | - | 500 | ms |

DC Electrical Characteristics


| Parameter | Description | Condition | Min | Typ | Max | Unit |
|--------------------------------|------------------------------------|--|--------------------|-----|--------------------|------|
| I _{OH} | Output high current (pin 3) | V _{OH} = V _{DD} - 0.5, V _{DD} = 3.3V (source) | 10 | 12 | - | mA |
| I _{OL} | Output low current (pin 3) | V _{OL} = 0.5, V _{DD} = 3.3V (sink) | 10 | 12 | - | mA |
| V _{IH} | Input high voltage (pin 1) | CMOS levels, 70% of V _{DD} | 0.7V _{DD} | - | V _{DD} | V |
| V _{IL} | Input low voltage (pin 1) | CMOS levels, 30% of V _{DD} | - | - | 0.3V _{DD} | V |
| I _{IH} | Input high current (pin 1) | V _{in} = V _{DD} | - | - | 10 | µA |
| I _{IL} | Input low current (pin 1) | V _{in} = V _{SS} | - | - | 10 | µA |
| I _{OZ} | Output leakage current (pin 3) | Three-state output, OE = 0 | -10 | - | 10 | µA |
| C _{IN} ^[2] | Input capacitance (pin 1) | Pin 1, or OE | - | 5 | 7 | pF |
| I _{VDD} | Supply current | V _{DD} = 3.3V, SSCLK = 10 to 166 MHz, C _{LOAD} = 0, OE = V _{DD} | - | - | 50 | mA |
| Δf/f | Initial accuracy at room temp. | T _A = 25°C, 3.3V | -25 | - | 25 | ppm |
| | Freq. stability over temp. range | T _A = -20°C to 70°C, 3.3V | -25 | - | 25 | ppm |
| | Freq. stability over voltage range | 3.0 to 3.6V | -12 | - | 12 | ppm |
| | Aging | T _A = 25°C, First year | -5 | - | 5 | ppm |

AC Electrical Characteristics^[2]

| Parameter | Description | Condition | Min | Typ | Max | Unit |
|------------------|-------------------------------------|--|-----|-----|--------------|------|
| DC | Output Duty Cycle | SSCLK, Measured at $V_{DD}/2$ | 45 | 50 | 55 | % |
| t_R | Output Rise Time | 20%–80% of V_{DD} , $C_L = 15$ pF | – | – | 2.7 | ns |
| t_F | Output Fall Time | 20%–80% of V_{DD} , $C_L = 15$ pF | – | – | 2.7 | ns |
| $T_{CCJ1}^{[3]}$ | Cycle-to-Cycle Jitter SSCLK (Pin 3) | SSCLK ≥ 133 MHz, Measured at $V_{DD}/2$ | – | 85 | 200 | ps |
| | | 25 MHz \leq SSCLK < 133 MHz, Measured at $V_{DD}/2$ | – | 215 | 400 | ps |
| | | SSCLK < 25 MHz, Measured at $V_{DD}/2$ | – | – | 1% of 1/SSCK | s |
| T_{OE1} | Output Disable Time (pin1 = OE) | Time from falling edge on OE to stopped outputs (Asynchronous) | – | 150 | 350 | ns |
| T_{OE2} | Output Enable Time (pin1 = OE) | Time from rising edge on OE to outputs at a valid frequency (Asynchronous) | – | 150 | 350 | ns |
| T_{LOCK} | PLL Lock Time | Time for SSCLK to reach valid frequency | – | – | 10 | ms |

Application Circuit

Figure 1. Application Circuit Diagram



Note

- 2. Guaranteed by characterization, not fully tested.
- 3. Jitter is configuration dependent. Actual jitter depends upon output frequencies, spread percentage, temperature, and output load. For more information, see the application note, "Jitter in PLL Based Systems: Causes, Effects, and Solutions" available at <http://www.cypress.com/clock/appnotes.html> or contact your local Cypress Field Application Engineer.

Switching Waveforms

Figure 2. Duty Cycle Waveform




Figure 3. Output Rise/Fall Time Waveform









Figure 4. Output Enable/Disable Timing Waveforms



Informational Graphs [4]




Notes

4. The "Informational Graphs" are meant to convey typical performance levels. No performance specifications are implied or guaranteed. Refer to the tables on pages three and four for device specifications.


Ordering Information

| Part Number | Package Description | Product Flow |
|------------------------------|---------------------------------------|--------------------------|
| Lead-free (Pb-free) | | |
| CY25701FLXCT ^[5] | 4-Lead Ceramic LCC SMD -Tape and Reel | Commercial, -20° to 70°C |
| CY25701FLXIT ^[5] | 4-Lead Ceramic LCC SMD -Tape and Reel | Industrial, -40° to 85°C |
| CY25701LXCZZT ^[6] | 4-Lead Ceramic LCC SMD -Tape and Reel | Commercial, -20° to 70°C |
| CY25701LXIZZT ^[6] | 4-Lead Ceramic LCC SMD -Tape and Reel | Industrial, -40° to 85°C |

Actual Marking^[7]



Package Drawings and Dimensions



Notes

- "FLX" suffix is used for products programmed in the field by Cypress distributors.
- "ZZZ" denotes the assigned product dash number. This number is assigned by the factory after the output frequency and spread percent programming data is received from the customer.
- Temp can be C (Com'l) or I (Industrial).

Document History Page

| Document Title: CY25701 Programmable High-frequency Crystal Oscillator with Spread Spectrum(SSXO) and No Spread Spectrum(XO) Option Document Number: 001-07313 | | | | |
|---|---------|------------|-----------------|---|
| REV. | ECN NO. | Issue Date | Orig. of Change | Description of Change |
| ** | 442944 | See ECN | RGL | New data sheet |
| *A | 487736 | See ECN | KKVTMP | Added Industrial temp |
| *B | 1414203 | See ECN | DPF/VED | Replaced the Package Drawing and Dimension figure on page seven and various copy edits; the reference to the software is now CyberClocksOnline™ rather than CyberClocks software. |

© Cypress Semiconductor Corporation, 2007. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А