

## SMD 0805, Glass Protected NTC Thermistors



### FEATURES

- TCR ranging from - 6 %/K at - 40 °C to - 2 %/K at 150 °C
- Tolerance on  $R_{25}$  down to 1 %, and on  $B_{25/85}$  down to 1 %
- Suitable for wave or reflow soldering
- NiSn terminations
- Fully glass coated and protected
- cUL recognized for safety applications (file E148885)
- AEC-Q200 qualified
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

### APPLICATIONS

- Temperature sensing, protection and compensation in automotive, industrial, telecom and consumer applications. Examples are:
  - Battery chargers
  - Power suppliers
  - Office equipment
  - LCD compensation
  - In-car entertainment

### DESCRIPTION

Size 0805 chip thermistors with a negative temperature coefficient. The device has no marking.

### PACKAGING

Available in 8 mm punched paper tape on reel package of 4000 units.

### DESIGN-IN SUPPORT

For complete Curve Computation, visit:

[www.vishay.com/resistors-non-linear/curve-computation-list/](http://www.vishay.com/resistors-non-linear/curve-computation-list/)

| QUICK REFERENCE DATA                      |                    |      |
|---|--------------------|------|
| PARAMETER                                 | VALUE              | UNIT |
| Resistance value at 25 °C                 | 2.2K to 680K       | Ω    |
| Tolerance on $R_{25}$ -value              | ± 1; ± 2; ± 3; ± 5 | %    |
| $B_{25/85}$ -value                        | 3430 to 4125       | K    |
| Tolerance on $B_{25/85}$ -value           | ± 1; ± 3           | %    |
| Maximum dissipation at 25 °C              | 210                | mW   |
| Thermal time constant $\tau$              | ≈ 10               | s    |
| Dissipation factor D                      | 3.5                | mW/K |
| Operating temperature range at zero power | - 40 to + 150      | °C   |
| Weight                                    | ≈ 0.008            | g    |

| ELECTRICAL DATA AND ORDERING INFORMATION |                        |                              |  |  |
|--|------------------------|------------------------------|--|--|
| $R_{25}$ -VALUE (kΩ)                     | $B_{25/85}$ -VALUE (K) | TOLERANCE ON $B_{25/85}$ (%) | SAP MATERIAL AND ORDERING NUMBER NTCS0805E3... (1) | 12NC OLD MATERIAL NUMBER 2381 615 5... (2) |
| 2.2                                      | 3600                   | ± 1                          | 222*MT   | *222                                       |
| 4.7                                      | 3500                   | ± 1                          | 472*MT   | *472                                       |
| 10                                       | 3430                   | ± 3                          | 103*LT   | -  |
| 10                                       | 3570                   | ± 3                          | 103*MT   | *103                                       |
| 10                                       | 3940                   | ± 1                          | 103*HT   | -  |
| 15                                       | 3700                   | ± 1                          | 153*MT   | *153                                       |
| 22                                       | 3800                   | ± 1                          | 223*HT   | *223                                       |
| 33                                       | 3920                   | ± 1                          | 333*HT   | *333                                       |
| 47                                       | 3960                   | ± 1                          | 473*HT   | *473                                       |
| 68                                       | 4100                   | ± 1                          | 683*XT   | *683                                       |
| 100                                      | 3590                   | ± 1                          | 104*MT   | -  |
| 100                                      | 4100                   | ± 1                          | 104*XT   | *104                                       |
| 330                                      | 3930                   | ± 1                          | 334*HT   | *334                                       |
| 470                                      | 4025                   | ± 1                          | 474*XT   | *474                                       |
| 680                                      | 4125                   | ± 1                          | 684*XT   | *684                                       |

#### Notes

(1) Replace \* in SAP by J for 5 %, H for 3 %, G for 2 %, F for 1 % tolerance on  $R_{25}$

(2) Replace \* in 12NC by 3 for 5 %, 6 for 3 %, 4 for 2 %, 5 for 1 % tolerance on  $R_{25}$



**DIMENSIONS** in millimeters



| L <sub>1</sub> | W           | T          | L <sub>2</sub> AND L <sub>3</sub> MIN. | L <sub>4</sub> MIN. |
|----------------|-------------|------------|--|---------------------|
| 2.0 ± 0.2      | 1.25 ± 0.15 | 0.8 ± 0.15 | 0.2                                    | 0.55                |

For complete Curve Computation, visit: [www.vishay.com/resistors-non-linear/curve-computation-list/](http://www.vishay.com/resistors-non-linear/curve-computation-list/)

| <b>RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES WITH R<sub>25</sub> AT 2.2 kΩ AND 4.7 kΩ</b> |                                 |           |                                 |           |  |
|--|---------------------------------|-----------|---------------------------------|-----------|--|
| T <sub>OPER</sub> (°C)   | PART NUMBER<br>NTCS0805E3222*MT |           | PART NUMBER<br>NTCS0805E3472*MT |           | ΔR/R DUE TO B <sub>tol.</sub><br>(± %) |
|  | R <sub>T</sub> (Ω)              | TCR (%/K) | R <sub>T</sub> (Ω)              | TCR (%/K) |  |
| -40  | 57 658                          | - 6.26    | 101 275                         | - 5.75    | 7.58                                   |
| -35  | 42 410                          | - 6.03    | 76 325                          | - 5.57    | 6.83                                   |
| -30  | 31 537                          | - 5.82    | 58 034                          | - 5.39    | 6.13                                   |
| -25  | 23 698                          | - 5.61    | 44 505                          | - 5.22    | 5.45                                   |
| -20  | 17 986                          | - 5.42    | 34 413                          | - 5.06    | 4.80                                   |
| -15  | 13 782                          | - 5.23    | 26 821                          | - 4.91    | 4.18                                   |
| -10  | 10 657                          | - 5.06    | 21 065                          | - 4.76    | 3.58                                   |
| -5   | 8312.0                          | - 4.89    | 16 667                          | - 4.61    | 3.01                                   |
| 0  | 6537.1                          | - 4.72    | 13 280                          | - 4.47    | 2.46                                   |
| 5  | 5182.1                          | - 4.57    | 10 654                          | - 4.34    | 1.93                                   |
| 10   | 4139.2                          | - 4.42    | 8603.2                          | - 4.21    | 1.42                                   |
| 15   | 3330.1                          | - 4.28    | 6991.1                          | - 4.09    | 0.93                                   |
| 20   | 2697.8                          | - 4.14    | 5715.6                          | - 3.97    | 0.46                                   |
| 25   | 2200.0                          | - 4.02    | 4700.0                          | - 3.86    | 0.00                                   |
| 30   | 1805.5                          | - 3.89    | 3886.6                          | - 3.75    | 0.22                                   |
| 35   | 1490.7                          | - 3.77    | 3231.2                          | - 3.64    | 0.43                                   |
| 40   | 1237.9                          | - 3.66    | 2700.3                          | - 3.54    | 0.64                                   |
| 45   | 1033.7                          | - 3.55    | 2267.9                          | - 3.44    | 0.84                                   |
| 50   | 867.85                          | - 3.45    | 1913.9                          | - 3.35    | 1.03                                   |
| 55   | 732.31                          | - 3.35    | 1622.6                          | - 3.26    | 1.22                                   |
| 60   | 620.96                          | - 3.25    | 1381.7                          | - 3.17    | 1.40                                   |
| 65   | 529.02                          | - 3.16    | 1181.7                          | - 3.09    | 1.58                                   |
| 70   | 452.73                          | - 3.07    | 1014.7                          | - 3.01    | 1.75                                   |
| 75   | 389.13                          | - 2.99    | 874.85                          | - 2.93    | 1.92                                   |
| 80   | 335.85                          | - 2.90    | 757.13                          | - 2.85    | 2.08                                   |
| 85   | 291.02                          | - 2.83    | 657.67                          | - 2.78    | 2.23                                   |
| 90   | 253.15                          | - 2.75    | 573.31                          | - 2.71    | 2.54                                   |
| 95   | 221.03                          | - 2.68    | 501.48                          | - 2.64    | 2.85                                   |
| 100  | 193.66                          | - 2.61    | 440.10                          | - 2.58    | 3.14                                   |
| 105  | 170.27                          | - 2.54    | 387.47                          | - 2.52    | 3.43                                   |
| 110  | 150.20                          | - 2.48    | 342.18                          | - 2.46    | 3.71                                   |
| 115  | 132.91                          | - 2.41    | 303.09                          | - 2.40    | 3.98                                   |
| 120  | 117.98                          | - 2.35    | 269.24                          | - 2.34    | 4.24                                   |
| 125  | 105.03                          | - 2.20    | 239.83                          | - 2.29    | 4.50                                   |
| 130  | 93.766                          | - 2.24    | 214.20                          | - 2.23    | 4.76                                   |
| 135  | 83.943                          | - 2.19    | 191.82                          | - 2.18    | 5.00                                   |
| 140  | 75.349                          | - 2.13    | 172.20                          | - 2.13    | 5.25                                   |
| 145  | 67.807                          | - 2.08    | 154.96                          | - 2.09    | 5.48                                   |
| 150  | 61.172                          | - 2.04    | 139.78                          | - 2.04    | 5.71                                   |



For complete Curve Computation, visit: [www.vishay.com/resistors-non-linear/curve-computation-list/](http://www.vishay.com/resistors-non-linear/curve-computation-list/)

| RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES WITH R <sub>25</sub> AT 10 kΩ |                                 |              |                                 |              |                                 |              |  |
|--|---------------------------------|--------------|---------------------------------|--------------|---------------------------------|--------------|--|
| T <sub>OPER</sub><br>(°C)  | PART NUMBER<br>NTCS0805E3103*LT |              | PART NUMBER<br>NTCS0805E3103*MT |              | PART NUMBER<br>NTCS0805E3103*HT |              | ΔR/R DUE TO B <sub>tol.</sub><br>(± %) |
|  | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) |  |
| - 40   | 182 928                         | - 5.47       | 232 634                         | - 5.92       | 335 922                         | - 6.60       | 11.22                                  |
| - 35   | 139 839                         | - 5.28       | 173 538                         | - 5.71       | 242 721                         | - 6.40       | 10.14                                  |
| - 30   | 107 902                         | - 5.10       | 130 769                         | - 5.51       | 177 179                         | - 6.19       | 9.10                                   |
| - 25   | 83 986                          | - 4.93       | 99 489                          | - 5.33       | 130 625                         | - 6.00       | 8.11                                   |
| - 20   | 65 904                          | - 4.77       | 76 385                          | - 5.15       | 97 234                          | - 5.81       | 7.15                                   |
| - 15   | 52 111                          | - 4.62       | 59 157                          | - 4.98       | 73 056                          | - 5.63       | 6.24                                   |
| - 10   | 41 501                          | - 4.48       | 46 194                          | - 4.82       | 55 387                          | - 5.45       | 5.35                                   |
| - 5  | 33 276                          | - 4.35       | 36 356                          | - 4.67       | 42 358                          | - 5.28       | 4.50                                   |
| 0  | 26 851                          | - 4.23       | 28 829                          | - 4.52       | 32 666                          | - 5.11       | 3.68                                   |
| 5  | 21 799                          | - 4.11       | 23 025                          | - 4.38       | 25 396                          | - 4.96       | 2.89                                   |
| 10   | 17 798                          | - 4.00       | 18 515                          | - 4.25       | 19 898                          | - 4.80       | 2.13                                   |
| 15   | 14 612                          | - 3.89       | 14 986                          | - 4.12       | 15 708                          | - 4.66       | 1.40                                   |
| 20   | 12 058                          | - 3.79       | 12 205                          | - 4.00       | 12 490                          | - 4.51       | 0.69                                   |
| 25   | 10 000                          | - 3.69       | 10 000                          | - 3.88       | 10 000                          | - 4.38       | 0.00                                   |
| 30   | 8332.5                          | - 3.60       | 8240.3                          | - 3.77       | 8060.1                          | - 4.25       | 0.66                                   |
| 35   | 6974.6                          | - 3.51       | 6827.5                          | - 3.66       | 6538.4                          | - 4.12       | 1.31                                   |
| 40   | 5863.2                          | - 3.43       | 5686.6                          | - 3.56       | 5336.7                          | - 4.00       | 1.93                                   |
| 45   | 4949.5                          | - 3.35       | 4760.3                          | - 3.46       | 4381.9                          | - 3.88       | 2.53                                   |
| 50   | 4194.8                          | - 3.27       | 4004.2                          | - 3.37       | 3618.5                          | - 3.77       | 3.11                                   |
| 55   | 3568.8                          | - 3.19       | 3383.8                          | - 3.28       | 3004.5                          | - 3.67       | 3.68                                   |
| 60   | 3047.5                          | - 3.12       | 2872.3                          | - 3.19       | 2507.9                          | - 3.56       | 4.23                                   |
| 65   | 2611.5                          | - 3.05       | 2448.5                          | - 3.11       | 2104.1                          | - 3.46       | 4.76                                   |
| 70   | 2245.5                          | - 2.99       | 2095.9                          | - 3.03       | 1774.0                          | - 3.37       | 5.28                                   |
| 75   | 1937.2                          | - 2.92       | 1801.2                          | - 2.95       | 1502.7                          | - 3.27       | 5.78                                   |
| 80   | 1676.6                          | - 2.86       | 1553.8                          | - 2.88       | 1278.7                          | - 3.18       | 6.27                                   |
| 85   | 1455.4                          | - 2.80       | 1345.3                          | - 2.81       | 1092.8                          | - 3.10       | 6.74                                   |
| 90   | 1267.2                          | - 2.74       | 1168.9                          | - 2.74       | 937.89                          | - 3.02       | 7.20                                   |
| 95   | 1106.5                          | - 2.68       | 1019.2                          | - 2.67       | 808.21                          | - 2.94       | 7.65                                   |
| 100  | 968.83                          | - 2.63       | 891.48                          | - 2.61       | 699.18                          | - 2.86       | 8.09                                   |
| 105  | 850.57                          | - 2.53       | 782.28                          | - 2.54       | 607.15                          | - 2.79       | 8.51                                   |
| 110  | 748.69                          | - 2.53       | 688.56                          | - 2.48       | 529.14                          | - 2.71       | 8.93                                   |
| 115  | 660.67                          | - 2.48       | 607.85                          | - 2.43       | 462.78                          | - 2.65       | 9.33                                   |
| 120  | 584.42                          | - 2.43       | 538.14                          | - 2.37       | 406.10                          | - 2.58       | 9.73                                   |
| 125  | 518.20                          | - 2.38       | 477.73                          | - 2.32       | 357.54                          | - 2.52       | 10.11                                  |
| 130  | 460.53                          | - 2.34       | 425.24                          | - 2.26       | 315.77                          | - 2.45       | 10.48                                  |
| 135  | 410.19                          | - 2.29       | 379.49                          | - 2.21       | 279.73                          | - 2.39       | 10.85                                  |
| 140  | 366.15                          | - 2.25       | 339.51                          | - 2.17       | 248.53                          | - 2.34       | 11.20                                  |
| 145  | 327.52                          | - 2.21       | 304.47                          | - 2.12       | 221.44                          | - 2.28       | 11.55                                  |
| 150  | 293.56                          | - 2.17       | 273.69                          | - 2.07       | 197.84                          | - 2.23       | 11.89                                  |



For complete Curve Computation, visit: [www.vishay.com/resistors-non-linear/curve-computation-list/](http://www.vishay.com/resistors-non-linear/curve-computation-list/)

| <b>RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES WITH R<sub>25</sub> AT 15 kΩ, 22 kΩ AND 47 kΩ</b> |                                 |              |                                 |              |                                 |              |  |
|---|---------------------------------|--------------|---------------------------------|--------------|---------------------------------|--------------|--|
| T <sub>OPER</sub><br>(°C)   | PART NUMBER<br>NTCS0805E3153*MT |              | PART NUMBER<br>NTCS0805E3223*HT |              | PART NUMBER<br>NTCS0805E3333*MT |              | ΔR/R DUE TO B <sub>tol.</sub><br>(± %) |
|   | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) |  |
| - 40  | 391 251                         | - 6.14       | 641 004                         | - 6.40       | 1 104 739                       | - 6.79       | 7.58                                   |
| - 35  | 289 245                         | - 5.94       | 468 038                         | - 6.18       | 793 249                         | - 6.53       | 6.83                                   |
| - 30  | 215 960                         | - 5.75       | 345 469                         | - 5.97       | 576 683                         | - 6.28       | 6.13                                   |
| - 25  | 162 779                         | - 5.56       | 257 644                         | - 5.77       | 424 161                         | - 6.05       | 5.45                                   |
| - 20  | 123 815                         | - 5.38       | 194 045                         | - 5.57       | 315 430                         | - 5.84       | 4.80                                   |
| - 15  | 95 001                          | - 5.21       | 147 521                         | - 5.39       | 237 022                         | - 5.63       | 4.18                                   |
| - 10  | 73 505                          | - 5.05       | 113 159                         | - 5.22       | 179 865                         | - 5.44       | 3.58                                   |
| - 5   | 57 329                          | - 4.89       | 87 544                          | - 5.05       | 137 767                         | - 5.26       | 3.01                                   |
| 0   | 45 058                          | - 4.74       | 68 281                          | - 4.89       | 106 459                         | - 5.08       | 2.46                                   |
| 5   | 35 674                          | - 4.60       | 53 672                          | - 4.74       | 82 958                          | - 4.92       | 1.93                                   |
| 10  | 28 445                          | - 4.46       | 42 503                          | - 4.59       | 65 162                          | - 4.76       | 1.42                                   |
| 15  | 22 834                          | - 4.33       | 33 898                          | - 4.46       | 51 572                          | - 4.61       | 0.93                                   |
| 20  | 18 450                          | - 4.20       | 27 220                          | - 4.32       | 41 112                          | - 4.47       | 0.46                                   |
| 25  | 15 000                          | - 4.08       | 22 000                          | - 4.20       | 33 000                          | - 4.34       | 0.00                                   |
| 30  | 12 268                          | - 3.96       | 17 892                          | - 4.07       | 26 663                          | - 4.21       | 0.22                                   |
| 35  | 10 092                          | - 3.85       | 14 638                          | - 3.96       | 21 678                          | - 4.08       | 0.43                                   |
| 40  | 8347.4                          | - 3.74       | 12 045                          | - 3.84       | 17 730                          | - 3.97       | 0.64                                   |
| 45  | 6941.1                          | - 3.64       | 9965.0                          | - 3.74       | 14 585                          | - 3.86       | 0.84                                   |
| 50  | 5801.1                          | - 3.54       | 8288.3                          | - 3.63       | 12 063                          | - 3.75       | 1.03                                   |
| 55  | 4872.1                          | - 3.44       | 6928.4                          | - 3.54       | 10 030                          | - 3.65       | 1.22                                   |
| 60  | 4111.1                          | - 3.35       | 5819.8                          | - 3.44       | 8381.6                          | - 3.55       | 1.40                                   |
| 65  | 3484.7                          | - 3.26       | 4911.4                          | - 3.35       | 7037.8                          | - 3.45       | 1.58                                   |
| 70  | 2966.6                          | - 3.18       | 4163.4                          | - 3.26       | 5936.8                          | - 3.36       | 1.75                                   |
| 75  | 2536.2                          | - 3.09       | 3544.6                          | - 3.18       | 5030.3                          | - 3.27       | 1.92                                   |
| 80  | 2176.9                          | - 3.02       | 3030.2                          | - 3.10       | 4280.4                          | - 3.19       | 2.08                                   |
| 85  | 1875.8                          | - 2.94       | 2600.9                          | - 3.02       | 3657.2                          | - 3.11       | 2.23                                   |
| 90  | 1622.5                          | - 2.87       | 2241.0                          | - 2.94       | 3137.1                          | - 3.03       | 2.54                                   |
| 95  | 1408.4                          | - 2.79       | 1938.0                          | - 2.87       | 2701.2                          | - 2.96       | 2.85                                   |
| 100   | 1226.8                          | - 2.73       | 1682.0                          | - 2.80       | 2334.4                          | - 2.89       | 3.14                                   |
| 105   | 1072.3                          | - 2.66       | 1464.9                          | - 2.73       | 2024.4                          | - 2.82       | 3.43                                   |
| 110   | 940.20                          | - 2.60       | 1280.0                          | - 2.67       | 1761.6                          | - 2.75       | 3.71                                   |
| 115   | 827.00                          | - 2.54       | 1122.0                          | - 2.60       | 1538.0                          | - 2.69       | 3.98                                   |
| 120   | 729.62                          | - 2.48       | 986.60                          | - 2.54       | 1346.9                          | - 2.63       | 4.24                                   |
| 125   | 645.60                          | - 2.42       | 870.11                          | - 2.48       | 1183.23                         | - 2.57       | 4.50                                   |
| 130   | 572.86                          | - 2.36       | 769.60                          | - 2.43       | 1042.4                          | - 2.51       | 4.76                                   |
| 135   | 509.71                          | - 2.31       | 682.59                          | - 2.37       | 921.02                          | - 2.45       | 5.00                                   |
| 140   | 454.71                          | - 2.26       | 607.05                          | - 2.32       | 815.99                          | - 2.40       | 5.25                                   |
| 145   | 406.69                          | - 2.21       | 541.28                          | - 2.27       | 724.85                          | - 2.35       | 5.48                                   |
| 150   | 364.64                          | - 2.16       | 483.86                          | - 2.22       | 645.54                          | - 2.30       | 5.71                                   |

For complete Curve Computation, visit: [www.vishay.com/resistors-non-linear/curve-computation-list/](http://www.vishay.com/resistors-non-linear/curve-computation-list/)



RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES WITH R25 AT 47 kΩ, 68 kΩ AND 100 kΩ

Table with 10 columns: Toper (°C), Part Number (NTCS0805E3473\*HT, NTCS0805E3683\*XT, NTCS0805E3104\*MT, NTCS0805E3104\*XT), RT (Ω), TCR (%/K), and ΔR/R Due to Btot. (± %). Rows range from -40°C to 150°C.



For complete Curve Computation, visit: [www.vishay.com/resistors-non-linear/curve-computation-list/](http://www.vishay.com/resistors-non-linear/curve-computation-list/)

| <b>RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES WITH R<sub>25</sub> AT 330 kΩ, 470 kΩ AND 680 kΩ</b> |                                 |              |                                 |              |                                 |              |  |
|--|---------------------------------|--------------|---------------------------------|--------------|---------------------------------|--------------|--|
| T <sub>OPER</sub><br>(°C)  | PART NUMBER<br>NTCS0805E3334*HT |              | PART NUMBER<br>NTCS0805E3474*XT |              | PART NUMBER<br>NTCS0805E3684*XT |              | ΔR/R DUE TO B <sub>tol.</sub><br>(± %) |
|  | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) | R <sub>T</sub><br>(Ω)           | TCR<br>(%/K) |  |
| - 40   | 10 488                          | - 6.53       | 16 325                          | - 6.70       | 23 477                          | - 6.58       | 7.58                                   |
| - 35   | 7608.4                          | - 6.31       | 11 742                          | - 6.48       | 16 980                          | - 6.38       | 6.83                                   |
| - 30   | 5579.1                          | - 6.10       | 8539.8                          | - 6.26       | 12 404                          | - 6.18       | 6.13                                   |
| - 25   | 4133.1                          | - 5.90       | 6276.8                          | - 6.05       | 9147.1                          | - 6.00       | 5.45                                   |
| - 20   | 3092.0                          | - 5.71       | 4660.3                          | - 5.86       | 6807.4                          | - 5.82       | 4.80                                   |
| - 15   | 2334.8                          | - 5.53       | 3493.6                          | - 5.67       | 5110.7                          | - 5.65       | 4.18                                   |
| - 10   | 1778.8                          | - 5.35       | 2643.2                          | - 5.49       | 3869.3                          | - 5.48       | 3.58                                   |
| - 5  | 1366.9                          | - 5.19       | 2017.4                          | - 5.32       | 2953.2                          | - 5.33       | 3.01                                   |
| 0  | 1058.9                          | - 5.03       | 1552.8                          | - 5.15       | 2271.5                          | - 5.17       | 2.46                                   |
| 5  | 826.75                          | - 4.87       | 1204.7                          | - 5.00       | 1760.2                          | - 5.03       | 1.93                                   |
| 10   | 650.33                          | - 4.73       | 941.99                          | - 4.85       | 1373.89                         | - 4.89       | 1.42                                   |
| 15   | 515.22                          | - 4.59       | 741.96                          | - 4.70       | 1079.7                          | - 4.75       | 0.93                                   |
| 20   | 410.99                          | - 4.45       | 588.54                          | - 4.56       | 854.12                          | - 4.62       | 0.46                                   |
| 25   | 330.00                          | - 4.33       | 470.00                          | - 4.43       | 680.00                          | - 4.50       | 0.00                                   |
| 30   | 266.64                          | - 4.20       | 377.77                          | - 4.31       | 544.69                          | - 4.38       | 0.22                                   |
| 35   | 216.75                          | - 4.08       | 305.53                          | - 4.18       | 438.89                          | - 4.26       | 0.43                                   |
| 40   | 177.22                          | - 3.97       | 248.58                          | - 4.07       | 355.64                          | - 4.15       | 0.64                                   |
| 45   | 145.70                          | - 3.86       | 203.40                          | - 3.96       | 289.76                          | - 4.04       | 0.84                                   |
| 50   | 120.43                          | - 3.76       | 167.35                          | - 3.85       | 237.33                          | - 3.94       | 1.03                                   |
| 55   | 100.06                          | - 3.66       | 138.42                          | - 3.75       | 195.38                          | - 3.84       | 1.22                                   |
| 60   | 83.541                          | - 3.56       | 115.06                          | - 3.65       | 161.62                          | - 3.75       | 1.40                                   |
| 65   | 70.081                          | - 3.47       | 96.120                          | - 3.55       | 134.33                          | - 3.65       | 1.58                                   |
| 70   | 59.059                          | - 3.38       | 80.672                          | - 3.46       | 112.16                          | - 3.56       | 1.75                                   |
| 75   | 49.989                          | - 3.29       | 68.012                          | - 3.37       | 94.052                          | - 3.48       | 1.92                                   |
| 80   | 42.491                          | - 3.21       | 57.588                          | - 3.29       | 79.204                          | - 3.39       | 2.08                                   |
| 85   | 36.265                          | - 3.13       | 48.966                          | - 3.20       | 66.973                          | - 3.31       | 2.23                                   |
| 90   | 31.074                          | - 3.05       | 41.803                          | - 3.12       | 56.855                          | - 3.24       | 2.54                                   |
| 95   | 26.726                          | - 2.98       | 35.826                          | - 3.05       | 48.449                          | - 3.16       | 2.85                                   |
| 100  | 23.070                          | - 2.91       | 30.819                          | - 2.97       | 41.439                          | - 3.09       | 3.14                                   |
| 105  | 19.985                          | - 2.84       | 26.608                          | - 2.90       | 35.569                          | - 3.02       | 3.43                                   |
| 110  | 17.371                          | - 2.77       | 23.053                          | - 2.83       | 30.636                          | - 2.95       | 3.71                                   |
| 115  | 15.149                          | - 2.71       | 20.039                          | - 2.77       | 26.474                          | - 2.89       | 3.98                                   |
| 120  | 13.253                          | - 2.64       | 17.477                          | - 2.70       | 22.952                          | - 2.82       | 4.24                                   |
| 125  | 11.630                          | - 2.58       | 15.290                          | - 2.64       | 19.961                          | - 2.76       | 4.50                                   |
| 130  | 10.236                          | - 2.52       | 13.417                          | - 2.58       | 17.412                          | - 2.70       | 4.76                                   |
| 135  | 9.0345                          | - 2.47       | 11.808                          | - 2.53       | 15.233                          | - 2.65       | 5.00                                   |
| 140  | 7.9963                          | - 2.41       | 10.422                          | - 2.47       | 13.364                          | - 2.59       | 5.25                                   |
| 145  | 7.0964                          | - 2.36       | 9.2239                          | - 2.42       | 11.757                          | - 2.54       | 5.48                                   |
| 150  | 6.3142                          | - 2.31       | 8.1851                          | - 2.36       | 10.371                          | - 2.48       | 5.71                                   |

### SOLDERING CONDITIONS

This SMD thermistor is only suitable for wave or reflow soldering, in accordance with JEDEC J-STD-020. The maximum temperature of 260 °C during 40 s should not be exceeded.

Typical examples of a soldering processes that will provide reliable joints without damage, are shown below.



Dimensions of the solder lands



### TESTS AND REQUIREMENTS

| SOLDERABILITY AND RESISTANCE TO SOLDERING HEAT |                |                              |                |                             |
|--|----------------|------------------------------|----------------|-----------------------------|
| IEC 60068-2-58                                 | TEST METHOD    | TEST                         | PROCEDURE      | REQUIREMENTS                |
| 6  | T <sub>C</sub> | Solderability                | 2 s at 235 °C  | Min. 95 % of surface wetted |
|  |                | Resistance to soldering heat | 10 s at 260 °C | $\Delta R/R < 5 \%$         |

### PACKAGING

#### TAPE SPECIFICATIONS

All tape specifications are in accordance with IEC 60286-3. Basic dimensions are given below. Carrier tape material is paper.

#### PAPER TAPE



DIMENSIONS OF PAPER TAPE in millimeters

| PARAMETER                     | DIMENSION | TOLERANCE |
|-------------------------------|-----------|-----------|
| A <sub>0</sub> <sup>(1)</sup> | 1.7       | ± 0.2     |
| B <sub>0</sub> <sup>(1)</sup> | 2.35      | ± 0.1     |
| W                             | 8.0       | ± 0.2     |
| E <sub>1</sub>                | 1.75      | ± 0.1     |
| F                             | 3.5       | ± 0.05    |
| D <sub>0</sub>                | 1.55      | ± 0.05    |
| P <sub>0</sub> <sup>(2)</sup> | 4.0       | ± 0.1     |
| P <sub>1</sub>                | 4.0       | ± 0.1     |
| P <sub>2</sub>                | 2.0       | ± 0.05    |
| T tape thickness              | 1.1       | Max.      |
| T <sub>1</sub> cover tape     | < 0.1     | -         |

#### Notes

- (1) Measured 0.3 mm above base pocket
- (2) P<sub>0</sub> pitch cumulative error over any 10 pitches ± 1.0 mm



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А