800 MHz, 4:1 Analog Multiplexer

ADV3221/ADV3222

FEATURES

- Excellent ac performance
  - −3 dB bandwidth
    - 800 MHz (200 mV p-p)
    - 750 MHz (2 V p-p)
  - Slew rate: 2400 V/µs
- Low power: 75 mW, V_S = ±5 V
- Excellent video performance
  - 100 MHz, 0.1 dB gain flatness
  - 0.02% differential gain error/0.02° differential phase error (R_L = 150 Ω)
- ADV3221 is a pin-for-pin upgrade to the HA4344
- Gain = +1 (ADV3221) or gain = +2 (ADV3222)
- Low all hostile crosstalk of −85 dB @ 5 MHz, and −58 dB @ 100 MHz
- Latched control lines for synchronous switching
- High impedance output disable allows connection of multiple devices without loading the output bus
- 16-lead SOIC

APPLICATIONS

- Routing of high speed signals including
  - Video (NTSC, PAL, S, SECAM, YUV, RGB)
  - Compressed video (MPEG, wavelet)
  - 3-level digital video (HDB3)
- Data communications
- Telecommunications

FUNCTIONAL BLOCK DIAGRAM



Figure 1.

GENERAL DESCRIPTION

The ADV3221 and ADV3222 are high speed, high slew rate, buffered 4:1 analog multiplexers. They offer a −3 dB signal bandwidth greater than 800 MHz and channel switch times of less than 20 ns with 1% settling. With lower than −58 dB of crosstalk and −67 dB isolation (at 100 MHz), the ADV3221 and ADV3222 are useful in many high speed applications. The differential gain error of less than 0.02% and differential phase error of less than 0.02°, together with 0.1 dB gain flatness out to 100 MHz while driving a 75 Ω back terminated load, make the ADV3221 and ADV3222 ideal for all types of signal switching.

The ADV3221/ADV3222 include an output buffer that can be placed into a high impedance state. This allows multiple outputs to be connected together for cascading stages without the off channels loading the output bus. The ADV3221 has a gain of +1, and the ADV3222 has a gain of +2; they both operate on ±5 V supplies while consuming less than 7.5 mA of idle current. The channel switching is performed via latched control lines, allowing synchronous updating in a multiple ADV3221/ADV3222 environment.

The ADV3221/ADV3222 are offered in a 16-lead SOIC package and are available over the extended industrial temperature range of −40°C to +85°C.

Rev. 0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 www.analog.com
Fax: 781.461.3113
©2010 Analog Devices, Inc. All rights reserved.

TABLE OF CONTENTS

Features 1
Applications 1
Functional Block Diagram 1
General Description 1
Revision History 2
Specifications 3
Timing and Logic Characteristics 4
Absolute Maximum Ratings 6
Thermal Resistance 6
Power Dissipation 6
ESD Caution 6
Pin Configuration and Function Descriptions 7
Typical Performance Characteristics 8
Circuit Diagrams 16
Theory of Operation 17
Applications Information 18
$\overline{CK1}$/$\overline{CK2}$ Operation 18
Circuit Layout 18
Termination 18
Capacitive Load 18
Outline Dimensions 19
Ordering Guide 19

REVISION HISTORY

3/10—Revision 0: Initial Version

SPECIFICATIONS

V_S = ±5 V, T_A = 25°C, R_L = 150 Ω, C_L = 2 pF, ADV3221 at G = +1, ADV3222 at G = +2, unless otherwise noted.

Table 1.

		ADV3221			ADV3222			
Parameter	**Test Conditions/Comments**	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Unit**
DYNAMIC PERFORMANCE								
−3 dB Bandwidth	200 mV p-p		1000			800		MHz
	2 V p-p		750			750		MHz
Gain Flatness	0.1 dB, 200 mV p-p		100			100		MHz
	0.1 dB, 2 V p-p		100			100		MHz
Propagation Delay	2 V p-p		700			650		ps
Settling Time	1%, 2 V step		5			5		ns
Slew Rate	2 V step, peak		2400			2700		V/µs
NOISE/DISTORTION PERFORMANCE								
Differential Gain Error	NTSC or PAL		0.01			0.02		%
Differential Phase Error	NTSC or PAL		0.01			0.02		Degrees
Crosstalk, All Hostile	f = 100 MHz		−87			−58		dB
	f = 5 MHz		−100			−85		dB
Off Isolation, Input to Output	f = 100 MHz, one channel		−67			−72		dB
Input Second-Order Intercept (ADV3222 Only)	f = 70 MHz, R_L = 100 Ω					54		dBm
Input Third-Order Intercept (ADV3222 Only)	f = 70 MHz, R_L = 100 Ω					17		dBm
Output 1 dB Compression Point (ADV3222 Only)	f = 70 MHz, R_L = 100 Ω					18.5		dBm
Input Voltage Noise	10 MHz to 100 MHz		16			17		nV/√Hz
DC PERFORMANCE								
Gain Error	No load			1			1	%
	R_L = 150 Ω		0.75			0.75		%
Gain Matching	Channel-to-channel, no load		1			1		%
OUTPUT CHARACTERISTICS								
Output Impedance	DC, enabled		0.02			0.04		Ω
	Disabled	1			1			MΩ
Output Disable Capacitance	Disabled		2.8			3		pF
Output Leakage Current	Disabled		2			2		µA
Output Voltage Range	No load	±2.9	±3		±2.9	±3		V
	R_L = 150 Ω	±2.8	±3		±2.75	±3		V
Short-Circuit Current			50			50		mA
INPUT CHARACTERISTICS								
Input Offset Voltage	Worst case (all configurations)		±5	±21		±5	±21	mV
Input Offset Voltage Drift			±10			±10		µV/°C
Input Voltage Range			±3			±1.5		V
Input Capacitance	Any switch configuration		1.8			1.8		pF
Input Resistance	Output enabled	1	10		1	10		MΩ
Input Bias Current	Output enabled		5	12		6	12	µA
SWITCHING CHARACTERISTICS								
Enable On Time			15			15		ns
Switching Time, 2 V Step	50% A0 to 1% settling		20			20		ns
Switching Transient (Glitch)	IN0 to IN1 switching		28			55		mV p-p

Parameter	Test Conditions/Comments	ADV3221 Min	ADV3221 Typ	ADV3221 Max	ADV3222 Min	ADV3222 Typ	ADV3222 Max	Unit
POWER SUPPLIES								
Supply Current	V+, output enabled, no load		7	8		7.5	9	mA
	V+, output disabled ($\overline{CS}$ high)		1.6	2.0		1.8	2.2	mA
	V−, output enabled, no load		7	8		7.5	9	mA
	V−, output disabled ($\overline{CS}$ high)		1.6	2.0		1.8	2.2	mA
Supply Voltage Range		±4.5		±5.5	±4.5		±5.5	V
Power Supply Rejection (PSR)	f = 100 kHz		−70			−65		dB
	f = 1 MHz		−60			−55		dB
TEMPERATURE								
Operating Temperature Range	Still air	−40		+85	−40		+85	°C
Junction-to-Ambient Thermal Impedance (θ_{JA})	Operating (still air)		81			81		°C/W

TIMING AND LOGIC CHARACTERISTICS

Table 2.

Parameter	Symbol	Min	Typ	Max	Unit
A0, A1, $\overline{CS}$ Setup Time	t_1	20			ns
$\overline{CK1}$ Pulse Width	t_2	40			ns
$\overline{CK1}$ to $\overline{CK2}$ Pulse Separation	t_3	40			ns
$\overline{CK2}$ Pulse Width	t_4	40			ns
A0, A1, $\overline{CS}$ Hold Time	t_5	20			ns

Table 3. Logic Levels

V_{IH}	V_{IL}	I_{IH}	I_{IL}	I_{IH}	I_{IL}
A0, A1, $\overline{CK1}$, $\overline{CK2}$, $\overline{CS}$	A0, A1, $\overline{CK1}$, $\overline{CK2}$, $\overline{CS}$	A0, A1, $\overline{CS}$	A0, A1, $\overline{CS}$	$\overline{CK1}$, $\overline{CK2}$	$\overline{CK1}$, $\overline{CK2}$
+2.0 V min	+0.8 V max	±2 µA max	±2 µA max	+60 µA max	+10 µA max

Timing and Programming Diagrams



Figure 2. Timing Diagram



Figure 3. Programming Example

ABSOLUTE MAXIMUM RATINGS

Table 4.

Parameter	Rating
Supply Voltage (V+ – V–)	12 V
Analog Input Voltage	V– to V+
Digital Input Voltage	0 V to V+
Output Voltage (Disabled Output)	(V+ – 1 V) to (V– + 1 V)
Output Short-Circuit Duration	Momentary
Output Short-Circuit Current	50 mA
Storage Temperature Range	–65°C to +150°C
Operating Temperature Range	–40°C to +85°C
Lead Temperature (Soldering, 10 sec)	300°C
Junction Temperature	150°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL RESISTANCE

θ_{JA} is specified for the worst-case conditions, that is, a device soldered in a circuit board for surface-mount packages.

Table 5. Thermal Resistance

Package Type	θ_{JA}	θ_{JC}	Unit
16-Lead Narrow-Body SOIC	81	43	°C/W

POWER DISSIPATION

The ADV3221/ADV3222 are operated with ±5 V supplies and can drive loads down to 150 Ω, resulting in a wide range of possible power dissipations. For this reason, extra care must be taken to adjust the operating conditions based on ambient temperature.

Packaged in a 16-lead narrow-body SOIC, the ADV3221 and ADV3222 junction-to-ambient thermal impedance (θ_{JA}) is 81°C/W. For long-term reliability, the maximum allowed junction temperature of the die, T_J, should not exceed 125°C. Temporarily exceeding this limit may cause a shift in parametric performance due to a change in stresses exerted on the die by the package. Figure 4 shows the range of the allowed internal die power dissipations that meet these conditions over the –40°C to +85°C ambient temperature range. When using Figure 4, do not include the external load power in the maximum power calculation, but do include the load current through the die output transistors.



Figure 4. Maximum Die Power Dissipation vs. Ambient Temperature

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS



Figure 5. Pin Configuration

Table 6. Pin Function Descriptions

Pin No.	Mnemonic	Description
1	IN0	Analog Input
2	GND	Ground
3	IN1	Analog Input
4	GND	Ground
5	IN2	Analog Input
6	GND	Ground
7	IN3	Analog Input
8	GND	Ground
9	V–	Negative Power Supply
10	$\overline{CK1}$	First Rank Clock
11	$\overline{CK2}$	Second Rank Clock
12	OUT	Analog Output
13	$\overline{CS}$	Chip Select (Output Enable)
14	A1	Select Address Most Significant Bit
15	A0	Select Address Least Significant Bit
16	V+	Positive Power Supply

Table 7. Truth Table

$\overline{CS}$	A1	A0	$\overline{CK1}$	$\overline{CK2}$	Output
0	0	0	0	0	IN0
0	0	1	0	0	IN1
0	1	0	0	0	IN2
0	1	1	0	0	IN3
1	X[1]	X[1]	0	0	High-Z

[1] X is don't care.

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 6. ADV3221 Small Signal Response vs. Capacitive Load, 200 mV p-p



Figure 9. ADV3222 Small Signal Response vs. Capacitive Load, 200 mV p-p



Figure 7. ADV3221 Large Signal Response vs. Capacitive Load, 2 V p-p



Figure 10. ADV3222 Large Signal Response vs. Capacitive Load, 2 V p-p



Figure 8. ADV3221 Small Signal Pulse Response vs. Capacitive Load, 200 mV p-p



Figure 11. ADV3222 Small Signal Pulse Response vs. Capacitive Load, 200 mV p-p



Figure 12. ADV3221 Large Signal Pulse Response vs. Capacitive Load, 2 V p-p



Figure 15. ADV3222 Large Signal Pulse Response vs. Capacitive Load, 2 V p-p



Figure 13. ADV3221 Large Signal Rising Slew Rate with 3 pF Load, 2 V p-p



Figure 16. ADV3222 Large Signal Rising Slew Rate with 3 pF Load, 2 V p-p



Figure 14. ADV3221 Large Signal Falling Slew Rate with 3 pF Load, 2 V p-p



Figure 17. ADV3222 Large Signal Falling Slew Rate with 3 pF Load, 2 V p-p



Figure 18. ADV3221 Switching Time



Figure 19. ADV3221 Enable Glitch



Figure 20. ADV3221 Enable On Timing



Figure 21. ADV3222 Switching Time



Figure 22. ADV3222 Enable Glitch



Figure 23. ADV3222 Enable On Timing



Figure 24. ADV3221 Disable Timing



Figure 27. ADV3222 Disable Timing



Figure 25. ADV3221 Switching Glitch Rising Edge



Figure 28. ADV3222 Switching Glitch Rising Edge



Figure 26. ADV3221 Switching Glitch Falling Edge



Figure 29. ADV3222 Switching Glitch Falling Edge



Figure 30. ADV3221 Settling Time, 2 V Step



Figure 33. ADV3222 Settling Time, 2 V Step



Figure 31. ADV3221 PSR



Figure 34. ADV3222 PSR



Figure 32. ADV3221 Output Noise vs. Frequency



Figure 35. ADV3222 Output Noise vs. Frequency



Figure 36. ADV3221 All Hostile Crosstalk



Figure 37. ADV3221 Crosstalk, Adjacent Channel



Figure 38. ADV3221 Off Isolation



Figure 39. ADV3222 All Hostile Crosstalk



Figure 40. ADV3222 Crosstalk, Adjacent Channel



Figure 41. ADV3222 Off Isolation



Figure 42. ADV3221/ADV3222 Input Impedance



Figure 43. ADV3221 Disabled Output Impedance



Figure 44. ADV3221 Enabled Output Impedance



Figure 45. ADV3221/ADV3222 S11 (Including Evaluation Board)



Figure 46. ADV3222 Disabled Output Impedance



Figure 47. ADV3222 Enabled Output Impedance



Figure 48. ADV3221 Overdrive Recovery



Figure 51. ADV3222 Overdrive Recovery



Figure 49. ADV3222 Harmonic Distortion, R_L = 100 Ω, C_L = 4 pF



Figure 52. ADV3222 Input Second-Order Intercept, R_L = 100 Ω, C_L = 4 pF



Figure 50. ADV3222 Input Third-Order Intercept, R_L = 100 Ω, C_L = 4 pF



Figure 53. ADV3222 Output P1dB, R_L = 100 Ω, C_L = 4 pF

CIRCUIT DIAGRAMS



Figure 54. ADV3221/ADV3222 Analog Input



Figure 55. ADV3221 Enabled Analog Output



Figure 56. ADV3222 Enabled Analog Output



Figure 57. ADV3221/ADV3222 Disabled Output



Figure 58. ADV3221/ADV3222 Logic Input



Figure 59. ADV3221/ADV3222 ESD Schematic

THEORY OF OPERATION

The ADV3221/ADV3222 are dual-supply, high performance 4:1 analog multiplexers, optimized for switching between multiple video sources. High peak slew rates enable wide bandwidth operation for large input signals. Internal compensation provides for high phase margin, allowing low overshoot and fast settling for pulsed inputs. Low enabled and disabled power consumption make the ADV3221 and ADV3222 ideal for constructing larger arrays.

The ADV3221/ADV3222 are organized as four input transconductance stages tied in parallel with a single output transimpedance stage followed by a unity-gain buffer. Internal voltage feedback sets the gain. The ADV3221 is configured as a gain of 1, while the ADV3222 uses a resistive feedback network and ground buffer to realize gain-of-two operation (see Figure 60).



Figure 60. Conceptual Diagram of ADV3222

When not in use, the output can be placed in a low power, high impedance disabled mode via the $\overline{CS}$ logic input. This is useful when paralleling multiple ADV3221/ADV3222 devices in a system to create larger switching arrays.

Switching between the inputs is controlled with the A0, A1, and $\overline{CS}$ logic inputs, which are latched through two stages of asynchronous latches. $\overline{CK1}$ controls the first stage latch, and $\overline{CK2}$ controls the second stage latch. The latch state is dependent on the level of the $\overline{CK1}$ and $\overline{CK2}$ signals, and it is not edge triggered. When using multiple ADV3221/ADV3222 devices in a switch design, this double buffered logic allows the use of the $\overline{CK2}$ signal to simultaneously update all ADV3221/ADV3222 devices in a system. The A0 and A1 logic inputs select which input is connected to the output (A1 is the most significant bit, A0 is the least significant bit), and the $\overline{CS}$ logic input determines whether the output is enabled or disabled.

APPLICATIONS INFORMATION

The ADV3221 and ADV3222 are high speed multiplexers used to switch video or RF signals. The low output impedance of the ADV3221/ADV3222 allows the output environment to be optimized for use in 75 Ω or 50 Ω systems by choosing the appropriate series termination resistor. For composite video applications, the ADV3222 (gain of +2) is typically used to provide compensation for the loss of the output termination.

$\overline{CK1}$/$\overline{CK2}$ OPERATION

The ADV3221/ADV3222 provide a double latched architecture for the A0, A1 (channel selection) and $\overline{CS}$ (output enable) logic. This allows for simultaneous update of multiple devices in bank switching applications or large multiplexer systems consisting of multiple devices connected to common output busses.

Holding $\overline{CK1}$ and $\overline{CK2}$ low places the ADV3221/ADV3222 in a transparent mode. In transparent mode, all logic changes to A0, A1, and $\overline{CS}$ immediately affects the input selection and output enable/disable.

CIRCUIT LAYOUT

Use of proper high speed design techniques is important to ensure optimum performance. Use a low inductance ground plane for power supply bypassing and to provide high quality return paths for the input and output signals. For best performance, it is recommended that power supplies be bypassed with 0.1 µF ceramic capacitors as close to the body of the device as possible. To provide stored energy for lower frequency, high current output driving, place 10 µF tantalum capacitors farther from the device.

The input and output signal paths should be stripline or microstrip controlled impedance. Video systems typically use 75 Ω characteristic impedance, whereas RF systems typically use 50 Ω. Various calculators are available to calculate the trace geometry required to produce the proper characteristic impedance.

TERMINATION

For a controlled impedance situation, termination resistors are required at the inputs and output of the device. The input termination should be a shunt resistor to ground with a value matching the characteristic impedance of the input trace. To reduce reflections, place the input termination resistor as close to the device input pin as possible. To minimize the input-to-input crosstalk, it is important to utilize a low inductance shield between input traces to isolate each input. Consideration of ground current paths must be taken to minimize loop currents in the shields to prevent them from providing a coupling medium for crosstalk.

For proper matching, the output series termination resistor should be the same value as the characteristic impedance of the output trace and placed as close to the output of the device as possible. This placement reduces the high frequency effect of series parasitic inductance, which can affect gain flatness and −3 dB bandwidth.

CAPACITIVE LOAD

A high frequency output can have difficulties when driving a large capacitive load, usually resulting in peaking in the frequency domain or overshoot in the time domain. If these effects become too large, oscillation can result.

The response of the device under various capacitive loads is shown in Figure 6 through Figure 12, and in Figure 15. If a condition arises where excessive load capacitance is encountered and the overshoot is too great or the device oscillates, a small series resistor of a few tens of ohms can be used to improve the performance.

OUTLINE DIMENSIONS



Figure 61. 16-Lead Standard Small Outline Package [SOIC_N]
Narrow Body
[R-16]
Dimensions shown in millimeters and (inches)

ORDERING GUIDE

Model[1]	Temperature Range	Package Description	Package Option
ADV3221ARZ	−40°C to +85°C	16-Lead SOIC_N	R-16
ADV3221ARZ-RL	−40°C to +85°C	16-Lead SOIC_N, 13″ Reel	R-16
ADV3221ARZ-R7	−40°C to +85°C	16-Lead SOIC_N, 7″ Reel	R-16
ADV3222ARZ	−40°C to +85°C	16-Lead SOIC_N	R-16
ADV3222ARZ-RL	−40°C to +85°C	16-Lead SOIC_N, 13″ Reel	R-16
ADV3222ARZ-R7	−40°C to +85°C	16-Lead SOIC_N, 7″ Reel	R-16
ADV3221-EVALZ		Evaluation Board	
ADV3222-EVALZ		Evaluation Board	

[1] Z = RoHS Compliant Part.

NOTES

©2010 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D08652-0-3/10(0)

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А