

# NS5B1G384

## Single (NC) Normally Closed SPST Analog Switch

The NS5B1G384 is Single Pole Single Throw (SPST) high-speed TTL-compatible switch. The low resistance and capacitance characteristics of this switch make it ideal for low-distortion audio, video, and data routing applications. The switch has a normally closed logic configuration meaning the switch is on (NC connected to COM) when IN is low. These switches are available in 5-pin SC-70 and 5-pin TSOP-5 (SOT23-5) packages for operation over the industrial (-40°C to +85°C) temperature range.

### Features

- $V_{CC}$  Operating Range: 2.0 V to 5.5 V
- Low On Resistance :  $R_{ON}$ : 4.0  $\Omega$  Typical @  $V_{CC} = 4.5$  V
- Minimal Propagation Delay :  $t_{pd} < 0.5$  ns
- Control Input Compatible with TTL Levels
- ESD Performance: Human Body Model  $> \pm 2$  kV
- 5-Pin SC-70 or 5-Pin TSOP-5 Packages Available
- These are Pb-Free Devices

### Typical Applications

- Audio, Video, and High-Speed Data Switching
- Mobile Phones
- Portable Devices
- Desktop & Notebook Computing




**ON Semiconductor®**

<http://onsemi.com>


### MARKING DIAGRAMS



**SC-70  
CASE 419A**




**TSOP-5  
(SOT23-5)  
CASE 483**




AG = For SC-70  
AD = For TSOP-5  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### LOGIC DIAGRAM



### PIN ASSIGNMENTS



### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

# NS5B1G384

## PIN DESCRIPTION

| PIN # | Name            | Direction | Description                 |
|-------|-----------------|-----------|-----------------------------|
| 1     | COM             | I/O       | Common Signal Line          |
| 2     | NC              | I/O       | Normally Closed Signal Line |
| 3     | GND             | Input     | Ground                      |
| 4     | IN              | Input     | Control Signal Line         |
| 5     | V <sub>CC</sub> | Input     | Voltage Supply              |

## TRUTH TABLE

| IN Control Input | Function                 |
|------------------|--------------------------|
| L                | NC Connected to COM      |
| H                | NC Disconnected from COM |

## MAXIMUM RATINGS

| Symbol              | Pins            | Rating                           | Value                         | Condition      | Unit |
|---------------------|-----------------|----------------------------------|-------------------------------|----------------|------|
| V <sub>CC</sub>     | V <sub>CC</sub> | Positive DC Supply Voltage       | −0.5 to +7.0                  |                | V    |
| V <sub>IS</sub>     | NC or COM       | Analog Signal Voltage            | −0.5 to V <sub>CC</sub> + 0.5 |                | V    |
| V <sub>IN</sub>     | IN              | Control Input Voltage            | −0.5 to +7.0                  |                | V    |
| I <sub>IS_CON</sub> | NC or COM       | Analog Signal Continuous Current | ± 300                         | Closed Switch  | mA   |
| I <sub>IS_PK</sub>  | NC or COM       | Analog Signal Peak Current       | ± 500                         | 10% Duty Cycle | mA   |
| I <sub>IN</sub>     | IN              | Control Input Current            | ± 20                          |                | mA   |
| T <sub>STG</sub>    |                 | Storage Temperature Range        | −65 to 150                    |                | °C   |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Pins            | Parameter                   | Value                  | Condition               | Unit |
|---------------------------------|-----------------|-----------------------------|------------------------|-------------------------|------|
| V <sub>CC</sub>                 | V <sub>CC</sub> | Positive DC Supply Voltage  | 2.0 to 5.5             |                         | V    |
| V <sub>IS</sub>                 | NC or COM       | Analog Signal Voltage       | GND to V <sub>CC</sub> |                         | V    |
| V <sub>IN</sub>                 | IN              | Control Input Voltage       | GND to 5.5             |                         | V    |
| T <sub>A</sub>                  |                 | Operating Temperature Range | −40 to +85             |                         | °C   |
| t <sub>r</sub> , t <sub>f</sub> |                 | Input Rise or Fall Time     | 20                     | V <sub>CC</sub> = 3.3 V | ns/V |
|                                 |                 |                             | 10                     | V <sub>CC</sub> = 5.0 V |      |

Minimum and maximum values are guaranteed through test or design across the **Recommended Operating Conditions**, where applicable. Typical values are listed for guidance only and are based on the particular conditions listed for each section, where applicable. These conditions are valid for all values found in the characteristics tables unless otherwise specified in the test conditions.

## ESD PROTECTION

| Pins     | Description      | Minimum Voltage |
|----------|------------------|-----------------|
| All Pins | Human Body Model | 2 kV            |

# NS5B1G384

## DC ELECTRICAL CHARACTERISTICS

### CONTROL INPUT (Typical: T = 25°C)

| Symbol          | Pins | Parameter             | Test Conditions                       | V <sub>CC</sub><br>(V) | -40°C to +85°C |      |      | Unit |
|-----------------|------|-----------------------|---------------------------------------|------------------------|----------------|------|------|------|
|                 |      |                       |                                       |                        | Min            | Typ  | Max  |      |
| V <sub>IH</sub> | IN   | Control Input High    |                                       | 4.5 – 5.5              | 2.0            |      |      | V    |
| V <sub>IL</sub> | IN   | Control Input Low     |                                       | 4.5 – 5.5              |                |      | 0.8  | V    |
| I <sub>IN</sub> | IN   | Control Input Leakage | 0 ≤ V <sub>IN</sub> ≤ V <sub>CC</sub> | 5.0                    |                | ±0.1 | ±0.5 | μA   |

### SUPPLY CURRENT AND LEAKAGE (Typical: T = 25°C)

| Symbol                    | Pins            | Parameter         | Test Conditions                                                                                             | V <sub>CC</sub><br>(V) | -40°C to +85°C |      |      | Unit |
|---------------------------|-----------------|-------------------|-------------------------------------------------------------------------------------------------------------|------------------------|----------------|------|------|------|
|                           |                 |                   |                                                                                                             |                        | Min            | Typ  | Max  |      |
| I <sub>NC</sub><br>(OFF)  | NC              | OFF State Leakage | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>V <sub>NC</sub> = 1.0 V<br>V <sub>COM</sub> = 4.5 V | 5.5                    |                | ±10  | ±100 | nA   |
| I <sub>COM</sub><br>(OFF) | COM             | OFF State Leakage | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>V <sub>NC</sub> = 4.5 V<br>V <sub>COM</sub> = 1.0 V | 5.5                    |                | ±10  | ±100 | nA   |
| I <sub>CC</sub>           | V <sub>CC</sub> | Quiescent Supply  | V <sub>IN</sub> and V <sub>IS</sub> = V <sub>CC</sub> or GND<br>I <sub>D</sub> = 0 A                        | 2.0 – 5.5              |                | ±0.1 | ±1.0 | μA   |
| I <sub>OFF</sub>          | IN              | Power Off Leakage | V <sub>IN</sub> = 5.5 V or GND                                                                              | 0                      |                | ±0.5 | ±1.0 | μA   |

### ON RESISTANCE (Typical: T = 25°C)

| Symbol          | Pins    | Parameter     | Test Conditions                                                                                                                                      | V <sub>CC</sub><br>(V) | -40°C to +85°C |                    |                  | Unit |
|-----------------|---------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|----------------|--------------------|------------------|------|
|                 |         |               |                                                                                                                                                      |                        | Min            | Typ                | Max              |      |
| R <sub>ON</sub> | NC, COM | ON Resistance | V <sub>IS</sub> = 0 V, I <sub>ON</sub> = 30 mA<br>V <sub>IS</sub> = 0 V, I <sub>ON</sub> = 64 mA<br>V <sub>IS</sub> = 2.4 V, I <sub>ON</sub> = 15 mA | 4.5<br>4.5<br>4.5      |                | 4.0<br>4.0<br>11.5 | 7.0<br>7.0<br>15 | Ω    |

# NS5B1G384

## AC ELECTRICAL CHARACTERISTICS

**TIMING/FREQUENCY** (Typical: T = 25°C, R<sub>L</sub> = 50 Ω, C<sub>L</sub> = 35 pF, f = 1 MHz)

| Symbol           | Pins      | Parameter         | Test Conditions                        | V <sub>CC</sub><br>(V) | -40°C to +85°C |     |     | Unit |
|------------------|-----------|-------------------|----------------------------------------|------------------------|----------------|-----|-----|------|
|                  |           |                   |                                        |                        | Min            | Typ | Max |      |
| t <sub>ON</sub>  | IN to NC  | Turn On Time      | As Above, Figures 1 and 2              | 4.5                    |                |     | 6.0 | ns   |
| t <sub>OFF</sub> | IN to NC  | Turn Off Time     | As Above, Figures 1 and 2              | 4.5                    |                |     | 2.0 | ns   |
| t <sub>pD</sub>  | NC to COM | Propagation Delay |                                        | 4.5                    |                |     | 0.5 | ns   |
| BW               |           | -3dB Bandwidth    | C <sub>L</sub> = 5 pF, Figures 3 and 4 | 4.5                    |                | 330 |     | MHz  |

**CAPACITANCE** (Typical: T = 25°C, R<sub>L</sub> = 50 Ω, C<sub>L</sub> = 5 pF, f = 1 MHz)

| Symbol           | Pins      | Parameter       | Test Conditions                                  | V <sub>CC</sub><br>(V) | -40°C to +85°C |     |     | Unit |
|------------------|-----------|-----------------|--------------------------------------------------|------------------------|----------------|-----|-----|------|
|                  |           |                 |                                                  |                        | Min            | Typ | Max |      |
| C <sub>IN</sub>  | IN        | Control Input   |                                                  | 0 V                    |                | 2.2 |     | pF   |
| C <sub>ON</sub>  | NC to COM | Through Switch  | V <sub>IN</sub> = 0V                             | 4.5 V                  |                | 12  |     | pF   |
| C <sub>OFF</sub> | NC        | Unselected Port | V <sub>IS</sub> = 4.5 V, V <sub>IN</sub> = 4.5 V | 4.5 V                  |                | 4.1 |     | pF   |

## DEVICE ORDERING INFORMATION

| Device Order Number | Package Type        | Tape & Reel Size <sup>†</sup> |
|---------------------|---------------------|-------------------------------|
| NS5B1G384DFT2G      | SC-70<br>(Pb-Free)  | 3000 / Tape & Reel            |
| NS5B1G384DTT1G      | TSOP-5<br>(Pb-Free) | 3000 / Tape & Reel            |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

## NS5B1G384




Figure 1.  $t_{ON}/t_{OFF}$





Figure 2.  $t_{ON}/t_{OFF}$



Channel switch control/s test socket is normalized. Off isolation is measured across an off channel. On loss is the bandwidth of an On switch.  $V_{ISO}$ , Bandwidth and  $V_{ONL}$  are independent of the input signal direction.


$$V_{ISO} = \text{Off Channel Isolation} = 20 \log \left( \frac{V_{OUT}}{V_{IN}} \right) \text{ for } V_{IN} \text{ at } 100 \text{ kHz}$$

$$V_{ONL} = \text{On Channel Loss} = 20 \log \left( \frac{V_{OUT}}{V_{IN}} \right) \text{ for } V_{IN} \text{ at } 100 \text{ kHz to } 50 \text{ MHz}$$


Bandwidth (BW) = the frequency 3 dB below  $V_{ONL}$

$V_{CT}$  = Use  $V_{ISO}$  setup and test to all other switch analog input/outputs terminated with 50 Ω


Figure 3. Off Channel Isolation/On Channel Loss (BW)/Crosstalk (On Channel to Off Channel)/ $V_{ONL}$



**Figure 4. Typical Bandwidth @  $V_{CC} = 5.5$  V,  $25^{\circ}\text{C}$**



**Figure 5. Off-Channel Isolation @  $V_{CC} = 5.5$  V,  $25^{\circ}\text{C}$**




**Figure 6. Typical Total Harmonic Distortion @  $V_{CC} = 4.5$  V**

# NS5B1G384

## PACKAGE DIMENSIONS

SC-88A (SC-70-5/SOT-353)  
CASE 419A-02  
ISSUE K



### NOTES:




1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |

# NS5B1G384

## PACKAGE DIMENSIONS

### TSOP-5, SOT23-5 CASE 483-02 ISSUE H




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 3.00        | BSC  |
| B   | 1.50        | BSC  |
| C   | 0.90        | 1.10 |
| D   | 0.25        | 0.50 |
| G   | 0.95        | BSC  |
| H   | 0.01        | 0.10 |
| J   | 0.10        | 0.26 |
| K   | 0.20        | 0.60 |
| L   | 1.25        | 1.55 |
| M   | 0°          | 10°  |
| S   | 2.50        | 3.00 |

#### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А