Mechanical Style Pressure Switch

Series IS1000

Long life: 5 million cycles



IS1000-01 IS1000-01-X202

Specifications


Model	IS1000-01
Proof pressure	
Max. pressure	
Operating pressure range	
Hysteresis	
Repeatability	
Contact	
Electrical entry	
Fluid	
Ambient and fluid temperature	
Port size	
Weight	

Switch Characteristics


Max. contact capacity	2V AC, 2W DC		
Voltage	24V AC/DC or less	48V AC/DC	100V AC/DC
Max. operating current	50mA	40mA	20mA
Shock resistance	30G		

Electrical Circuit

Up to 100V AC/DC



Operating Pressure Range



How to Order

IS1000 — 01 S [ ] — Q

[ ] R(PT) 1/8, NPT 1/8


Sealant

—	None
S	With sealant

Optional

X201	Lead wire length 3m
X202	Operating pressure range 0.1 to 0.6MPa
X215	Lead wire length 3m Operating pressure range 0.1 to 0.6MPa

Construction



Components

No.	Description	Material
①	Shield plate	Rolled steel plate
②	Switch ass'y	—
③	Piston	Oil polyacetal
④	PT fittings	Zinc die cast
⑤	Adjustment screw	Brass (Electrical nickel plated)
⑥	Pointer	Vinyl chloride
⑦	Spring	Stainless steel 304-WPB
⑧	Scale plate	Rigid vinyl chloride
⑨	Miniseal Y type	NBR
⑩	Magnet	Rare earth magnet

⚠ Precautions

Be sure to read before handling.
Refer to p.0-26 and 0-27 for Safety Instructions and common precautions, on the products mentioned in this catalogue and refer to p.3.0-7 to 3.0-9 for precautions on every series.


Wiring

⚠Warning

①Connect load before connecting with power source.
②In the case of induction load or lead wire exceeding 5m long, the following contact protection box should be used.

Part No.	Voltage	Lead wire length
CD-P11	100V AC	Switch side: 0.5m Load side: 0.5m
CD-P12	24V DC	

③Internal circuit of contact protection box




④How to connect contact protection box
Connect the lead wires from the body and the contact protective box side indicated "SWITCH".
Lead wire should be as short as possible, within 1m.

Installation/Piping

⚠Warning

①When changing piping by hand, hold body.
Electrical wire must not be subjected to excessive force.
②Do not drop nor apply an excessive force.
③Tighten IS1000-01 applying the spanner on the PT fitting part.



Air Supply

⚠Warning

①Do not use with corrosive gases or fluids.
②Avoid use in vacuum applications. Switch may implode.

Pressure Setting

⚠Caution

①Set pressure scale at the value of the Pressure drop.
②When detecting ON-pressure signal, note that set pressure on scale plate plus ON-OFF differencial (Hysteresis) will be ON-pressure signal.

Environment

⚠Warning

①Avoid using a switch in a magnetic environment. It may cause a malfunction.
②Do not use in an environment with water or splashing oil to avoid malfunction or damage to switch caused by corrosion of the electric circuit.

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А