# NHD-2.8-25664UCY2

## Graphic OLED Display Module

| | |
|---|---|
| NHD- | Newhaven Display |
| 2.8- | 2.8” diagonal size |
| 25664- | 256 x 64 pixel resolution |
| UC- | Model |
| Y- | Emitting Color: Yellow |
| 2- | +2.95V power supply |


**Newhaven Display International, Inc.**
**2511 Technology Drive, Suite 101**
**Elgin IL, 60124**
**Ph: 847-844-8795 Fax: 847-844-8796**

www.newhavendisplay.com
nhtech@newhavendisplay.com nhsales@newhavendisplay.com

## Document Revision History

| Revision | Date | Description | Changed by |
|---|---|---|---|
| 0 | 5/1/2011 | Initial Product Release | - |
| 1 | 2/22/2013 | Electrical characteristics and mechanical drawing updated | JN |

## Functions and Features

- **256 x 64 pixel resolution**
- **Built-in SSD1322 controller**
- **Parallel or serial MPU interface**
- **Single, low voltage power supply**
- **RoHS compliant**

## Mechanical Drawing




CONFIDENTIAL

The drawing contained herein is the exclusive property of Newhaven Display International, Inc. and shall not be copied, reproduced, and/or disclosed in any format without permission.

# Interface Description

**Parallel Interface:**

| Pin No. | Symbol | External Connection | Function Description |
|---|---|---|---|
| 1 | VSS | Power Supply | Ground |
| 2 | VDD | Power Supply | Supply Voltage for OLED and logic. |
| 3 | NC | - | No Connect |
| 4 | D/C | MPU | Register select signal. D/C=0: Command, D/C=1: Data |
| 5 | R/W or /WR | MPU | **6800-interface:**<br>Read/Write select signal, R/W=1: Read R/W: =0: Write<br>**8080-interface:**<br>Active LOW Write signal. |
| 6 | E or /RD | MPU | **6800-interface:**<br>Operation enable signal. Falling edge triggered.<br>**8080-interface:**<br>Active LOW Read signal. |
| 7-14 | DB0 – DB7 | MPU | 8-bit Bi-directional data bus lines. |
| 15 | NC | - | No Connect |
| 16 | /RES | MPU | Active LOW Reset signal. |
| 17 | /CS | MPU | Active LOW Chip Select signal. |
| 18 | NC | - | No Connect |
| 19 | BS1 | MPU | MPU Interface Select signal. |
| 20 | BS0 | MPU | MPU Interface Select signal. |

**Serial Interface:**

| Pin No. | Symbol | External Connection | Function Description |
|---|---|---|---|
| 1 | VSS | Power Supply | Ground |
| 2 | VDD | Power Supply | Supply Voltage for OLED and logic. |
| 3 | NC | - | No Connect |
| 4 | D/C | MPU | Register select signal. D/C=0: Command, D/C=1: Data<br>Tie LOW for 3-wire Serial Interface. |
| 5-6 | VSS | Power Supply | Ground |
| 7 | SCLK | MPU | Serial Clock signal. |
| 8 | SDIN | MPU | Serial Data Input signal. |
| 9 | NC | - | No Connect |
| 10-14 | VSS | Power Supply | Ground |
| 15 | NC | - | No Connect |
| 16 | /RES | MPU | Active LOW Reset signal. |
| 17 | /CS | MPU | Active LOW Chip Select signal. |
| 18 | NC | - | No Connect |
| 19 | BS1 | MPU | MPU Interface Select signal. |
| 20 | BS0 | MPU | MPU Interface Select signal. |

**MPU Interface Pin Selections**

| Pin Name | 6800 Parallel 8-bit interface | 8080 Parallel 8-bit interface | 3-wire Serial Interface | 4-wire Serial Interface |
|---|---|---|---|---|
| BS1 | 1 | 1 | 0 | 0 |
| BS0 | 1 | 0 | 1 | 0 |

**MPU Interface Pin Assignment Summery**

| Bus Interface | Data/Command Interface | | | | | | | | Control Signals | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | E | R/W | /CS | D/C | /RES |
| 8-bit 6800 | D[7:0] | | | | | | | | E | R/W | /CS | D/C | /RES |
| 8-bit 8080 | D[7:0] | | | | | | | | /RD | /WR | /CS | D/C | /RES |
| 3-wire SPI | Tie LOW | | | | | NC | SDIN | SCLK | Tie LOW | | /CS | Tie LOW | /RES |
| 4-wire SPI | Tie LOW | | | | | NC | SDIN | SCLK | Tie LOW | | /CS | D/C | /RES |

# Wiring Diagrams












## Electrical Characteristics

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| Operating Temperature Range | Top | Absolute Max | -40 | - | +85 | °C |
| Storage Temperature Range | Tst | Absolute Max | -40 | - | +90 | °C |
| | | | | | | |
| Supply Voltage | VDD | | 2.95 | - | 3.3 | V |
| Supply Current (logic) | IDD | Ta=25°C | 5 | - | 5 | mA |
| Supply Current (display) | ICC | 50% ON | 148 | - | 130 | mA |
| | | 100% ON | 244 | - | 215 | mA |
| Sleep Mode Current | $IDD+ICC_{SLEEP}$ | | - | - | 10 | µA |
| "H" Level input | Vih | | 0.8*VDD | - | VDD | V |
| "L" Level input | Vil | | VSS | - | 0.2*VDD | V |
| "H" Level output | Voh | | 0.9*VDD | - | VDD | V |
| "L" Level output | Vol | | VSS | - | 0.1*VDD | V |

## Optical Characteristics

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| Viewing Angle - Top | AV | | - | 80 | - | º |
| Viewing Angle – Bottom | AV | | - | 80 | - | º |
| Viewing Angle – Left | AH | | - | 80 | - | º |
| Viewing Angle – Right | AH | | - | 80 | - | º |
| Contrast Ratio | Cr | | 2000:1 | - | - | - |
| Response Time (rise) | Tr | - | - | 10 | - | us |
| Response Time (fall) | Tf | - | - | 10 | - | us |
| Brightness | | 50% checkerboard | 60 | 80 | - | $cd/m^2$ |
| Lifetime | | Ta=25°C, 50% checkerboard | 40,000 | - | - | Hrs |

**Note**: Lifetime at typical temperature is based on accelerated high-temperature operation. Lifetime is tested at average 50% pixels on and is rated as Hours until **Half-Brightness**. The Display OFF command can be used to extend the lifetime of the display.

Luminance of active pixels will degrade faster than inactive pixels. Residual (burn-in) images may occur. To avoid this, every pixel should be illuminated uniformly.

# Built-in SSD1322 controller
# Instruction Table

| Instruction | Code | | | | | | | | | | Description | RESET value |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | D/C | HEX | DB7 | DB6 | DB5 | DB4 | DB3 | DB2 | DB1 | DB0 | | |
| Enable Grayscale Table | 0 | **00** | **0** | **0** | **0** | **0** | **0** | **0** | **0** | **0** | Enable the Grayscale table settings. (see command 0xB8) | |
| Set Column Address | 0<br>1<br>1 | **15**<br>**A[6:0]**<br>**B[6:0]** | **0**<br>*<br>* | **0**<br>**A6**<br>**B6** | **0**<br>**A5**<br>**B5** | **1**<br>**A4**<br>**B4** | **0**<br>**A3**<br>**B3** | **1**<br>**A2**<br>**B2** | **0**<br>**A1**<br>**B1** | **1**<br>**A0**<br>**B0** | Set column start and end address<br>A[6:0]: Column start address. Range: 0-119d<br>B[6:0]: Column end address. Range: 0-119d | <br>0<br>119d |
| Write RAM Command | 0 | **5C** | **0** | **1** | **0** | **1** | **1** | **1** | **0** | **0** | Enable MCU to write Data into RAM | |
| Read RAM Command | 0 | **5D** | **0** | **1** | **0** | **1** | **1** | **1** | **0** | **1** | Enable MCU to read Data from RAM | |
| Set Row Address | 0<br>1<br>1 | **75**<br>**A[6:0]**<br>**B[6:0]** | **0**<br>*<br>* | **1**<br>**A6**<br>**B6** | **1**<br>**A5**<br>**B5** | **1**<br>**A4**<br>**B4** | **0**<br>**A3**<br>**B3** | **1**<br>**A2**<br>**B2** | **0**<br>**A1**<br>**B1** | **1**<br>**A0**<br>**B0** | Set row start and end address<br>A[6:0]: Row start address. Range: 0-127d<br>B[6:0]: Row end address. Range: 0-127d | <br>0<br>127d |
| Set Remap | 0<br>1<br>1 | **A0**<br>**A[5:0]**<br>**B[4]** | **1**<br>**0**<br>* | **0**<br>**0**<br>* | **1**<br>**A5**<br>**0** | **0**<br>**A4**<br>**B4** | **0**<br>**0**<br>**0** | **0**<br>**A2**<br>**0** | **0**<br>**A1**<br>**0** | **0**<br>**A0**<br>**1** | A[0] = 0; Horizontal Address Increment<br>A[0] = 1; Vertical Address Increment<br>A[1] = 0; Disable Column Address remap<br>A[1] = 1; Enable Column Address remap<br>A[2] = 0; Disable Nibble remap<br>A[2] = 1; Enable Nibble remap<br>A[4] = 0; Scan from COM0 to COM[N-1]<br>A[4] = 1; Scan from COM[N-1] to COM0<br>A[5] = 0; Disable COM split Odd/Even<br>A[5] = 1; Enable COM split Odd/Even<br>B[4] = 0; Disable Dual COM mode<br>B[4] = 1; Enable Dual COM mode<br>Note: A[5] must be 0 if B[4] is 1. | 0<br><br>0<br><br>0<br><br>0<br><br>0<br><br>0 |
| Set Display Start Line | 0<br>1 | **A1**<br>**A[6:0]** | **1**<br>* | **0**<br>**A6** | **1**<br>**A5** | **0**<br>**A4** | **0**<br>**A3** | **0**<br>**A2** | **0**<br>**A1** | **1**<br>**A0** | Set display RAM display start line register from 0-127. | 0 |
| Set Display Offset | 0<br>1 | **A2**<br>**A[6:0]** | **1**<br>* | **0**<br>**A6** | **1**<br>**A5** | **0**<br>**A4** | **0**<br>**A3** | **0**<br>**A2** | **1**<br>**A1** | **0**<br>**A0** | Set vertical shift by COM from 0~127. | 0 |
| Display Mode | 0 | **A4/A7** | **1** | **0** | **1** | **0** | **0** | **X2** | **X1** | **X0** | 0xA4 = Entire display OFF<br>0xA5 = Entire display ON, all pixels Grayscale level 15<br>0xA6 = Normal display<br>0xA7 = Inverse display | 0xA6 |
| Enable Partial Display | 0<br>1<br>1 | **A8**<br>**A[6:0]**<br>**B[6:0]** | **1**<br>**0**<br>**0** | **0**<br>**A6**<br>**B6** | **1**<br>**A5**<br>**B5** | **0**<br>**A4**<br>**B4** | **1**<br>**A3**<br>**B3** | **0**<br>**A2**<br>**B2** | **0**<br>**A1**<br>**B1** | **0**<br>**A0**<br>**B0** | Turns ON partial mode.<br>A[6:0] = Address of start row<br>B[6:0] = Address of end row (B[6:0] > A[6:0]) | |

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Exit Partial Display | 0 | **A9** | **1** | **0** | **1** | **0** | **1** | **0** | **0** | **1** | Exit Partial Display mode | |
| Function Selection | 0 | **AB** | **1** | **0** | **1** | **0** | **1** | **0** | **1** | **1** | A[0] = 0; External VDD | |
| | 1 | **A[0]** | **0** | **0** | **0** | **0** | **0** | **0** | **0** | **A0** | A[0] = 1; Internal VDD regulator | 1 |
| Set Sleep Mode ON/OFF | 0 | **AE~AF** | **1** | **0** | **1** | **0** | **1** | **1** | **1** | **X0** | 0xAE = Sleep Mode ON (display OFF)<br>0xAF = Sleep Mode OFF (display ON) | |
| Set Phase Length | 0 | **B1** | **1** | **0** | **1** | **1** | **0** | **0** | **0** | **1** | A[3:0] = P1. Phase 1 period of 5-31 DCLK clocks | 9 |
| | 1 | **A[7:0]** | **A7** | **A6** | **A5** | **A4** | **A3** | **A2** | **A1** | **A0** | A[7:4] = P2. Phase 2 period of 3-15 DCLK clocks | 7 |
| Set Display Clock Divide Ratio / Oscillator Frequency | 0 | **B3** | **1** | **0** | **1** | **1** | **0** | **0** | **1** | **1** | A[3:0] = 0000; divide by 1 | 0 |
| | 1 | **A[7:0]** | **A7** | **A6** | **A5** | **A4** | **A3** | **A2** | **A1** | **A0** | A[3:0] = 0001; divide by 2<br>A[3:0] = 0010; divide by 4<br>A[3:0] = 0011; divide by 8<br>A[3:0] = 0100; divide by 16<br>A[3:0] = 0101; divide by 32<br>A[3:0] = 0110; divide by 64<br>A[3:0] = 0111; divide by 128<br>A[3:0] = 1000; divide by 256<br>A[3:0] = 1001; divide by 512<br>A[3:0] = 1010; divide by 1024 | |
| | | | | | | | | | | | A[3:0] >= 1011; invalid | 1100b |
| | | | | | | | | | | | A[7:4] = Set the Oscillator Frequency. Frequency increases with the value of A[7:4]. Range 0000b~1111b. | |
| Set GPIO | 0 | **B5** | **1** | **0** | **1** | **1** | **0** | **1** | **0** | **1** | A[1:0] = 00; GPIO0 input disabled | |
| | 1 | **A[3:0]** | ***** | ***** | ***** | ***** | **A3** | **A2** | **A1** | **A0** | A[1:0] = 01; GPIO0 input enabled<br>A[1:0] = 10; GPIO0 output LOW | 10b |
| | | | | | | | | | | | A[1:0] = 11; GPIO0 output HIGH<br>A[3:2] = 00; GPIO1 input disabled<br>A[3:2] = 01; GPIO1 input enabled | |
| | | | | | | | | | | | A[3:2] = 10; GPIO1 output LOW | 10b |
| | | | | | | | | | | | A[3:2] = 11; GPIO1 output HIGH | |
| Set Second Precharge Period | 0 | **B6** | **1** | **0** | **1** | **1** | **0** | **1** | **1** | **0** | Sets the second precharge period | 1000b |
| | 1 | **A[3:0]** | ***** | ***** | ***** | ***** | **A3** | **A2** | **A1** | **A0** | A[3:0] = DCLKs | |
| Set Grayscale Table | 0 | **B8** | **1** | **0** | **1** | **1** | **1** | **0** | **0** | **0** | Sets the gray scale pulse width in units of DCLK. Range 0-180d. | |
| | 1 | **A1[7:0]** | **$A1_7$** | **$A1_6$** | **$A1_5$** | **$A1_4$** | **$A1_3$** | **$A1_2$** | **$A1_1$** | **$A1_0$** | A1[7:0] = Gamma Setting for GS1 | |
| | 1 | **A2[7:0]** | **$A2_7$** | **$A2_6$** | **$A2_5$** | **$A2_4$** | **$A2_3$** | **$A2_2$** | **$A2_1$** | **$A2_0$** | A2[7:0] = Gamma Setting for GS2 | |
| | 1 | **.** | **.** | **.** | **.** | **.** | **.** | **.** | **.** | **.** | . | |
| | 1 | **.** | **.** | **.** | **.** | **.** | **.** | **.** | **.** | **.** | . | |
| | 1 | **.** | **.** | **.** | **.** | **.** | **.** | **.** | **.** | **.** | . | |
| | 1 | **A14[7:0]** | **$A14_7$** | **$A14_6$** | **$A14_5$** | **$A14_4$** | **$A14_3$** | **$A14_2$** | **$A14_1$** | **$A14_0$** | A14[7:0] = Gamma Setting for GS14 | |
| | 1 | **A15[7:0]** | **$A15_7$** | **$A15_6$** | **$A15_5$** | **$A15_4$** | **$A15_3$** | **$A15_2$** | **$A15_1$** | **$A15_0$** | A15[7:0] = Gamma Setting for GS15 | |
| | | | | | | | | | | | Note: 0 < GS1 < GS2 < GS3 … < GS14 < GS15<br>The setting must be followed by command 0x00. | |
| Select Default | 0 | **B9** | **1** | **0** | **1** | **1** | **1** | **0** | **0** | **1** | Sets Linear Grayscale table | |

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Linear Gray Scale Table | | | | | | | | | | | GS0 pulse width = 0<br>GS0 pulse width = 0<br>GS0 pulse width = 8<br>GS0 pulse width = 16<br>.<br>.<br>.<br>GS0 pulse width = 104<br>GS0 pulse width = 112 | |
| Set Precharge Voltage | 0<br>1 | **BB**<br>**A[4:0]** | **1**<br>* | **0**<br>* | **1**<br>* | **1**<br>**A4** | **1**<br>**A3** | **0**<br>**A2** | **1**<br>**A1** | **1**<br>**A0** | Set precharge voltage level.<br>A[4:0] = 0x00; 0.20*VCC<br>.<br>.<br>A[4:0] = 0x3E; 0.60*VCC | 0x17 |
| Set VCOMH Voltage | 0<br>1 | **BE**<br>**A[3:0]** | **1**<br>* | **0**<br>* | **1**<br>* | **1**<br>* | **1**<br>**A3** | **1**<br>**A2** | **1**<br>**A1** | **0**<br>**A0** | Sets the VCOMH voltage level<br>A[3:0] = 0x00; 0.72*VCC<br>.<br>.<br>A[3:0] = 0x04; 0.8*VCC<br>.<br>.<br>A[3:0] = 0x07; 0.86*VCC | 0x04 |
| Set Contrast Control | 0<br>1 | **C1**<br>**A[7:0]** | **1**<br>**A7** | **1**<br>**A6** | **0**<br>**A5** | **0**<br>**A4** | **0**<br>**A3** | **0**<br>**A2** | **0**<br>**A1** | **1**<br>**A0** | Double byte command to select 1 out of 256 contrast steps.<br>Contrast increases as the value increases. | 0x7F |
| Master Contrast Control | 0<br>1 | **C7**<br>**A[3:0]** | **1**<br>* | **1**<br>* | **0**<br>* | **0**<br>* | **0**<br>**A3** | **1**<br>**A2** | **1**<br>**A1** | **1**<br>**A0** | A[3:0] = 0x00; Reduce output for all colors to 1/16<br>A[3:0] = 0x01; Reduce output for all colors to 2/16<br>.<br>.<br>A[3:0] = 0x0E; Reduce output for all colors to 15/16<br>A[3:0] = 0x0F; no change | 0x0f |
| Set Multiplex Ratio | 0<br>1 | **CA**<br>**A[6:0]** | **1**<br>* | **1**<br>**A6** | **0**<br>**A5** | **0**<br>**A4** | **1**<br>**A3** | **0**<br>**A2** | **1**<br>**A1** | **0**<br>**A0** | Set MUX ratio to N+1 MUX<br>N=A[6:0]; from 16MUX to 128MUX (0 to 14 are invalid) | 127d |
| Set Command Lock | 0<br>1 | **FD**<br>**A[2]** | **1**<br>**0** | **1**<br>**0** | **1**<br>**0** | **1**<br>**1** | **1**<br>**0** | **1**<br>**A2** | **0**<br>**1** | **1**<br>**0** | A[2] = 0; Unlock OLED to enable commands<br>A[2] = 1; Lock OLED from entering commands | 0x12 |

**For detailed instruction information, see datasheet:** http://www.newhavendisplay.com/app_notes/SSD1322.pdf

# MPU Interface

**For detailed timing information, see datasheet:** http://www.newhavendisplay.com/app_notes/SSD1322.pdf

## 6800-MPU Parallel Interface

The parallel interface consists of 8 bi-directional data pins, R/W, D/C, E, and /CS.
A LOW on R/W indicates write operation, and HIGH on R/W indicates read operation.
A LOW on D/C indicates "Command" read or write, and HIGH on D/C indicates "Data" read or write.
The E input serves as data latch signal, while /CS is LOW. Data is latched at the falling edge of E signal.

| Function | E | R/W | /CS | D/C |
|---|---|---|---|---|
| Write Command | ↓ | 0 | 0 | 0 |
| Read Status | ↓ | 1 | 0 | 0 |
| Write Data | ↓ | 0 | 0 | 1 |
| Read Data | ↓ | 1 | 0 | 1 |

## 8080-MPU Parallel Interface

The parallel interface consists of 8 bi-directional data pins, /RD, /WR, D/C, and /CS.
A LOW on D/C indicates "Command" read or write, and HIGH on D/C indicates "Data" read or write.
A rising edge of /RS input serves as a data read latch signal while /CS is LOW.
A rising edge of /WR input serves as a data/command write latch signal while /CS is LOW.

| Function | /RD | /WR | /CS | D/C |
|---|---|---|---|---|
| Write Command | 1 | ↑ | 0 | 0 |
| Read Status | ↑ | 1 | 0 | 0 |
| Write Data | 1 | ↑ | 0 | 1 |
| Read Data | ↑ | 1 | 0 | 1 |

Alternatively, /RD and /WR can be kept stable while /CS serves as the data/command latch signal.

| Function | /RD | /WR | /CS | D/C |
|---|---|---|---|---|
| Write Command | 1 | 0 | ↑ | 0 |
| Read Status | 0 | 1 | ↑ | 0 |
| Write Data | 1 | 0 | ↑ | 1 |
| Read Data | 0 | 1 | ↑ | 1 |

## Serial Interface (4-wire)

The 4-wire serial interface consists of serial clock SCLK, serial data SDIN, D/C, and /CS.
D0 acts as SCLK and D1 acts as SDIN. D2 should be left open. D3~D7, E, and R/W should be connected to GND.

| Function | /RD | /WR | /CS | D/C | D0 |
|---|---|---|---|---|---|
| Write Command | Tie LOW | Tie LOW | 0 | 0 | ↑ |
| Write Data | Tie LOW | Tie LOW | 0 | 1 | ↑ |

SDIN is shifted into an 8-bit shift register on every rising edge of SCLK in the order of D7, D6,…D0.
D/C is sampled on every eighth clock and the data byte in the shift register is written to the GDRAM or command register in the same clock.
Note: Read is not available in serial mode.

## Serial Interface (3-wire)

The 3-wire serial interface consists of serial clock SCLK, serial data SDIN, and /CS.
D0 acts as SCLK and D1 acts as SDIN. D2 should be left open. D3~D7, E, R/W, and D/C should be connected to GND.

| Function | /RD | /WR | /CS | D/C | D0 |
|---|---|---|---|---|---|
| Write Command | Tie LOW | Tie LOW | 0 | Tie LOW | ↑ |
| Write Data | Tie LOW | Tie LOW | 0 | Tie LOW | ↑ |

SDIN is shifted into an 9-bit shift register on every rising edge of SCLK in the order of D/C, D7, D6,…D0.
D/C (first bit of the sequential data) will determine if the following data byte is written to the Display Data RAM (D/C = 1) or the command register (D/C = 0).
Note: Read is not available in serial mode.

**For detailed protocol information, see datasheet:** http://www.newhavendisplay.com/app_notes/SSD1322.pdf

## Example Initialization Sequence:

```
Set_Command_Lock(0x12);                 // Unlock Basic Commands (0x12/0x16)
Set_Display_On_Off(0x00);               // Display Off (0x00/0x01)
Set_Column_Address(0x1C,0x5B);
Set_Row_Address(0x00,0x3F);
Set_Display_Clock(0x91);                // Set Clock as 80 Frames/Sec
Set_Multiplex_Ratio(0x3F);              // 1/64 Duty (0x0F~0x3F)
Set_Display_Offset(0x00);               // Shift Mapping RAM Counter (0x00~0x3F)
Set_Start_Line(0x00);                   // Set Mapping RAM Display Start Line (0x00~0x7F)
Set_Remap_Format(0x14);                 // Set Horizontal Address Increment
                                        //    Column Address 0 Mapped to SEG0
                                        //    Disable Nibble Remap
                                        //    Scan from COM[N-1] to COM0
                                        //    Disable COM Split Odd Even
                                        //    Enable Dual COM Line Mode
Set_GPIO(0x00);                         // Disable GPIO Pins Input
Set_Function_Selection(0x01);           // Enable Internal VDD Regulator
Set_Display_Enhancement_A(0xA0,0xFD);       // Enable External VSL
Set_Contrast_Current(0x9F);             // Set Segment Output Current
Set_Master_Current(0x0F);               // Set Scale Factor of Segment Output Current Control
//Set_Gray_Scale_Table();               // Set Pulse Width for Gray Scale Table
Set_Linear_Gray_Scale_Table();          //set default linear gray scale table
Set_Phase_Length(0xE2);                 // Set Phase 1 as 5 Clocks & Phase 2 as 14 Clocks
Set_Display_Enhancement_B(0x20);        // Enhance Driving Scheme Capability (0x00/0x20)
Set_Precharge_Voltage(0x1F);            // Set Pre-Charge Voltage Level as 0.60*VCC
Set_Precharge_Period(0x08);             // Set Second Pre-Charge Period as 8 Clocks
Set_VCOMH(0x07);                        // Set Common Pins Deselect Voltage Level as 0.86*VCC
Set_Display_Mode(0x02);                 // Normal Display Mode (0x00/0x01/0x02/0x03)
Set_Partial_Display(0x01,0x00,0x00);    // Disable Partial Display
Set_Display_On_Off(0x01);
```

# Quality Information

| Test Item | Content of Test | Test Condition | Note |
|---|---|---|---|
| High Temperature storage | Test the endurance of the display at high storage temperature. | +90°C , 240hrs | 2 |
| Low Temperature storage | Test the endurance of the display at low storage temperature. | -40°C , 240hrs | 1,2 |
| High Temperature Operation | Test the endurance of the display by applying electric stress (voltage & current) at high temperature. | +85°C 240hrs | 2 |
| Low Temperature Operation | Test the endurance of the display by applying electric stress (voltage & current) at low temperature. | -40°C , 240hrs | 1,2 |
| High Temperature / Humidity Operation | Test the endurance of the display by applying electric stress (voltage & current) at high temperature with high humidity. | +60°C , 90% RH , 240hrs | 1,2 |
| Thermal Shock resistance | Test the endurance of the display by applying electric stress (voltage & current) during a cycle of low and high temperatures. | -40°C,30min -> 25°C,5min -> 85°C,30min = 1 cycle<br>100 cycles | |
| Vibration test | Test the endurance of the display by applying vibration to simulate transportation and use. | 10-22Hz , 15mm amplitude.<br>22-500Hz, 1.5G<br>30min in each of 3 directions X,Y,Z | 3 |
| Atmospheric Pressure test | Test the endurance of the display by applying atmospheric pressure to simulate transportation by air. | 115mbar, 40hrs | 3 |
| Static electricity test | Test the endurance of the display by applying electric static discharge. | VS=800V, RS=1.5kΩ, CS=100pF<br>One time | |

**Note 1:** No condensation to be observed.
**Note 2:** Conducted after 2 hours of storage at 25°C, 0%RH.
**Note 3:** Test performed on product itself, not inside a container.
**Evaluation Criteria:**
1: Display is fully functional during operational tests and after all tests, at room temperature.
2: No observable defects.
3: Luminance >50% of initial value.
4: Current consumption within 50% of initial value

# Precautions for using OLEDs/LCDs/LCMs

See Precautions at www.newhavendisplay.com/specs/precautions.pdf

# Warranty Information and Terms & Conditions

http://www.newhavendisplay.com/index.php?main_page=terms

**Newhaven Display International, Inc. reserves the right to alter this product or specification at any time without notification.**

# OCEAN CHIPS
## Океан Электроники
## Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

**«JONHON»** (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

**«FORSTAR»** (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А