

Standard Surface-Mounting Slide DIP Switches



- Gold-plated twin contacts ensure high reliability.
- Washable, with seal tape available.
- Models with from 1 to 10 poles meet wide needs.
- Embossed taping available for small-reel 100 pcs/500 pcs.



RoHS Compliant

■List of Models

Tube Packaging

| No. of poles | Quantity per tube | Type | | Flat actuator | | Raised actuator |
|--------------|-------------------|------|-------------------|--|---|-----------------|
| | | | | Standard | With seal tape | |
| | | | |  |  | |
| 1 | 130 | | A6S-1101-H | A6S-1102-H | A6S-1104-H | |
| 2 | 76 | | A6S-2101-H | A6S-2102-H | A6S-2104-H | |
| 3 | 55 | | A6S-3101-H | A6S-3102-H | A6S-3104-H | |
| 4 | 42 | | A6S-4101-H | A6S-4102-H | A6S-4104-H | |
| 5 | 35 | | A6S-5101-H | A6S-5102-H | A6S-5104-H | |
| 6 | 28 | | A6S-6101-H | A6S-6102-H | A6S-6104-H | |
| 7 | 25 | | A6S-7101-H | A6S-7102-H | A6S-7104-H | |
| 8 | 22 | | A6S-8101-H | A6S-8102-H | A6S-8104-H | |
| 9 | 20 | | A6S-9101-H | A6S-9102-H | A6S-9104-H | |
| 10 | 18 | | A6S-0101-H | A6S-0102-H | A6S-0104-H | |

Note: Order in multiples of the package quantity.

Embossed Taping (Standard reel)

| Type | | Flat actuator | | Raised actuator | |
|--------------|-------------------|---|---|-------------------|---|
| | | Standard | With seal tape | | |
| No. of poles | Quantity per reel |  |  | Quantity per reel |  |
| | 800 | A6S-1101-PH | A6S-1102-PH | | 800 |
| 1 | 900 | A6S-2101-PH | A6S-2102-PH | 700 | A6S-2104-PH |
| 2 | | A6S-3101-PH | A6S-3102-PH | 700 | A6S-3104-PH |
| 3 | | A6S-4101-PH | A6S-4102-PH | 700 | A6S-4104-PH |
| 4 | | A6S-5101-PH | A6S-5102-PH | 800 | A6S-5104-PH |
| 5 | | A6S-6101-PH | A6S-6102-PH | 700 | A6S-6104-PH |
| 6 | | A6S-7101-PH | A6S-7102-PH | 800 | A6S-7104-PH |
| 7 | | A6S-8101-PH | A6S-8102-PH | 700 | A6S-8104-PH |
| 8 | | --- (See note 2.) | A6S-9102-PH | 700 | A6S-9104-PH |
| 9 | | --- (See note 2.) | A6S-0102-PH | 800 | A6S-0104-PH |
| 10 | | | | | |

Note: 1. Order in multiples of the package quantity.

2. Models with a different number of poles than those listed here can also be ordered. For details, consult your OMRON sales representative.

Embossed Taping (Small reel)

| Type | | Flat actuator | | Raised actuator | |
|--------------|-------------------|---|---|-------------------|---|
| | | Standard | With seal tape | | |
| No. of poles | Quantity per reel |  |  | Quantity per reel |  |
| | 400 | --- (See note 2.) | A6S-2102-PMH | | --- (See note 2.) |
| 2 | 400 | A6S-3101-PMH | --- | --- | --- |
| 3 | | A6S-4101-PMH | A6S-4102-PMH | A6S-4104-PMH | A6S-4104-PMH |
| 4 | | A6S-6101-PMH | A6S-6102-PMH | A6S-6104-PMH | A6S-6104-PMH |
| 6 | | A6S-8101-PMH | A6S-8102-PMH | A6S-8104-PMH | A6S-8104-PMH |
| 8 | | A6S-0101-PMH | A6S-0102-PMH | A6S-0104-PMH | A6S-0104-PMH |
| 10 | | | | | |

Note: 1. Order in multiples of the package quantity.

2. Models with a different number of poles than those listed here can also be ordered. For details, consult your OMRON sales representative.

Embossed Taping (100 pcs reel)

| Type | | Flat actuator | | Raised actuator | |
|--------------|-------------------|---|---|-------------------|---|
| | | Standard | With seal tape | | |
| No. of poles | Quantity per reel |  |  | Quantity per reel |  |
| | 100 | A6S-1101-H-R100 | A6S-1102-H-R100 | | 100 |
| 1 | 100 | A6S-2101-H-R100 | A6S-2102-H-R100 | 100 | A6S-2104-H-R100 |
| 2 | | A6S-3101-H-R100 | A6S-3102-H-R100 | 100 | A6S-3104-H-R100 |
| 3 | | A6S-4101-H-R100 | A6S-4102-H-R100 | 100 | A6S-4104-H-R100 |
| 4 | | A6S-5101-H-R100 | A6S-5102-H-R100 | 100 | A6S-5104-H-R100 |
| 5 | | A6S-6101-H-R100 | A6S-6102-H-R100 | 100 | A6S-6104-H-R100 |
| 6 | | A6S-7101-H-R100 | A6S-7102-H-R100 | 100 | A6S-7104-H-R100 |
| 7 | | A6S-8101-H-R100 | A6S-8102-H-R100 | 100 | A6S-8104-H-R100 |
| 8 | | A6S-9101-H-R100 | A6S-9102-H-R100 | 100 | A6S-9104-H-R100 |
| 9 | | A6S-0101-H-R100 | A6S-0102-H-R100 | 100 | A6S-0104-H-R100 |
| 10 | | | | | |

Ratings/Characteristics

| | |
|------------------------------------|--|
| Rating (resistive load) | 25 mA at 24 VDC 10 μ A (minimum current) at 3.5 VDC |
| Ambient operating temperature | -20 to +70°C at 60% max. (with no icing or condensation) |
| Ambient operating humidity | 35% to 95% (at +5 to +35°C) |
| Insulation resistance | 100 M Ω min. (at 250 VDC with insulation tester) |
| Contact resistance (initial value) | 200 m Ω max. |
| Dielectric strength | Between terminals 500 VAC for 1 min |
| Vibration resistance | Malfunction 10 to 55 Hz, 1.5-mm double amplitude |

| | | |
|----------------------|-------------|--|
| Shock resistance | Malfunction | 300 m/s ² min. |
| Durability | Electrical | 1,000 operations min. |
| Washing | | Standard models: Not possible, Models with seal tape: Possible, Models with raised actuators: Not possible |
| Degree of protection | | IEC IP40 |
| Operating force | | 0.29 to 9.8 N (30 to 1,000 gf) |
| Weight | | 0.25 g (2 poles) 0.41 g (4 poles) 0.58 g (6 poles) 0.73 g (8 poles) 0.87 g (10 poles) |

■Dimensions (Unit: mm)

● Flat Actuator

Standard

A6S-□101-H

A6S-□101-PH

A6S-□101-PMH

A6S-□101-H-R100



With Seal Tape

A6S-□102-H

A6S-□102-PH

A6S-□102-PMH

A6S-□102-H-R100



* 1 pole type is 0 to 0.15 mm


● Raised Actuator

A6S-□104-H

A6S-□104-PH

A6S-□104-PMH

A6S-□104-H-R100




PCB Dimensions (Reference)
(Top View)




P: Number of poles


Flat Actuator
Standard



Flat Actuator
With Seal Tape



Raised Actuator




| No. of poles | Model | | | Dimension A |
|--------------|---------------|----------------|-----------------|-------------|
| | Flat Actuator | | Raised Actuator | |
| | Standard | With Seal Tape | | |
| 1 | A6S-1101-H | A6S-1102-H | A6S-1104-H | 3.48 |
| 2 | A6S-2101-H | A6S-2102-H | A6S-2104-H | 6.02 |
| 3 | A6S-3101-H | A6S-3102-H | A6S-3104-H | 8.56 |
| 4 | A6S-4101-H | A6S-4102-H | A6S-4104-H | 11.10 |
| 5 | A6S-5101-H | A6S-5102-H | A6S-5104-H | 13.64 |
| 6 | A6S-6101-H | A6S-6102-H | A6S-6104-H | 16.18 |
| 7 | A6S-7101-H | A6S-7102-H | A6S-7104-H | 18.72 |
| 8 | A6S-8101-H | A6S-8102-H | A6S-8104-H | 21.26 |
| 9 | A6S-9101-H | A6S-9102-H | A6S-9104-H | 23.80 |
| 10 | A6S-0101-H | A6S-0102-H | A6S-0104-H | 26.34 |

Note: Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions.

■Internal Connections

Contact Form (Top View)



■Precautions

Be sure to read the Safety precautions common to all DIP Switches for correct use.

- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

OMRON Corporation
Electronic and Mechanical Components Company

Contact: www.omron.com/ecb

Cat. No. A211-E1-04
0619(0207)(O)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

[A6S-1102-H](#) [A6S-1102-PH](#) [A6S-3101-PH](#) [A6S-4104-PH](#) [A6S-8104-PH](#) [A6S-0101-H](#) [A6S-0102-H](#) [A6S-0102-PH](#)
[A6S-0104-H](#) [A6S-2101-H](#) [A6S-2101-PH](#) [A6S-2102-H](#) [A6S-2102-PH](#) [A6S-2104-H](#) [A6S-3101-H](#) [A6S-3102-H](#) [A6S-](#)
[3102-PH](#) [A6S-3104-H](#) [A6S-4101-H](#) [A6S-4102-H](#) [A6S-4102-PH](#) [A6S-4104-H](#) [A6S-5101-H](#) [A6S-5102-H](#) [A6S-5102-](#)
[PH](#) [A6S-5104-H](#) [A6S-6101-H](#) [A6S-6102-H](#) [A6S-6102-PH](#) [A6S-6104-H](#) [A6S-7101-H](#) [A6S-7102-H](#) [A6S-7102-PH](#)
[A6S-7104-H](#) [A6S-8101-H](#) [A6S-8102-H](#) [A6S-8102-PH](#) [A6S-8104-H](#) [A6S-9101-H](#) [A6S-9102-H](#) [A6S-9102-PH](#) [A6S-](#)
[9104-H](#) [A6S-1101-H](#) [A6S-4101-PH](#) [A6S-0104-PMH](#) [A6S-1104-H](#) [A6S-1104-PH](#) [A6S-2104-PH](#) [A6S-4101-PMH](#)
[A6S-5104-PH](#) [A6S-6101-PMH](#) [A6S-6104-PH](#) [A6S-6104-PMH](#) [A6S-8101-PH](#) [A6S-8101-PMH](#) [A6S-8104-PMH](#) [A6S-](#)
[7104-PH](#) [A6S-9104-PH](#) [A6S-2102-PMH](#) [A6S-8102-PMH](#) [A6S-4102-PMH](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А